

# LSI SAS 9210-8i

## 8-Port, 6Gb/s SAS+SATA to PCI Express Host Bus Adapter



LSI SAS 9210-8i

### 8-Port SAS HBA Provides High Performance for Internal Storage Connections

#### Overview

The LSI SAS 9210-8i host bus adapter provides high performance for internal drive connectivity in 1U and 2U servers and workstations. The LSI SAS 9210-8i provides 8 lanes of 6Gb/s SAS and is matched with 8 lanes of PCI Express 2.0 5Gb/s performance to eliminate bottlenecks. Performance is based on the LSISAS2008 IO controller that highly integrates the latest enhancements in PCI Express and SAS technology. The HBA supports up to 256 SAS or SATA devices.

The LSI SAS 9210-8i has two (x4) internal mini SAS connectors (SFF8087) that are vertically positioned enabling a low profile solution which provide SAS and SATA data transfer rates of 1.5, 3 and 6Gb/s per lane through automatic speed negotiation that can achieve over 320,000 IOPs. Enhanced features include T-10 Protection Information Model for early detection of and recovery from data corruption, and Spread Spectrum Clocking (SSC) for minimal EMI.

#### SAS Leadership

LSI offers the broadest SAS product portfolio in the industry with true end-to-end solutions including controllers, expanders, active-active multiplexers, ROCs, host bus adapters, RAID solutions, and external storage. LSI's proven SAS core has completed extensive stress and interoperability testing resulting in the industry's most robust, interoperable solution.

LSI has supplied leading edge serial technology to systems throughout the world for over seven generations, making LSI the most experienced enabler of serial interconnect for storage in the world. Integrators can be assured that their LSI adapter is providing the most advanced and robust serial technology available.

#### Fusion MPT Architecture

The LSI SAS host bus adapters are based on the Fusion MPT™ architected SAS controllers, which implements LSI's Fusion-MPT (Message Passing Technology) architecture. Each controller features embedded PowerPC™ processors that deliver maximum host CPU offload. The built-in intelligence enables LSI to publish a single binary OS driver to operate any Fusion MPT controller or adapter. The architecture enables high performance, reduced software development, and faster time to market.

#### KEY FEATURES

- 8 internal 6Gb/s SAS+SATA ports
- 8 lanes, PCI Express 2.0
- Low profile form factor design
- Two x4 internal mini-SAS connectors (SFF8087)
- Internal connectors vertically positioned on board
- LSISAS2008 6Gb/s SAS+SATA Controller
- Supports up to 256 SAS or SATA end devices
- Supports SSDs, HDDs and tape drives
- Offers Integrated RAID (0, 1, 1E and 10)

#### KEY ADVANTAGES

- Provides state of the art connectivity for servers and appliances with internal storage
- 8 lanes of PCI Express 2.0 provides fast signaling for high-bandwidth applications
- High performance with 6Gb/s data transfer rates

LSI SAS 9210-8i Host Bus Adapter		
I/O Controller	LSISAS2008/ Fusion MPT 2.0	
Storage Connectivity ; Data Transfer Rates	8 ports, 6Gb/s SAS 2.0 Compliant	
SAS Bandwidth	Half Duplex 600 MB/s per lane	
Port Configurations	8 ea, x1 ports (individual drives) 2 ea, x4 wide port	
Host Bus	x8 lane, PCI Express 2.0 compliant	
PCI Data Burst Transfer Rates	Half Duplex x8, PCIe, 4000 MB/s	
Physical Dimensions	Low Profile (2.6" x 6.6")	
Connectors	Two mini-SAS internal connectors (SFF8087) vertically positioned	
Brackets	Full height and low profile	
Cable Support	Passive Copper	
Host Bus Type	x8 lane, PCI Express 2.0	
PCI Card Type	3.3 V Add-in Card	
Operating Voltage	+12V +/-8%; 3.3V +/-8%	
PCI Power (Nominal)	7W typical (Airflow min 200 LFM)	
Device Support	256 Non-RAID SAS/SATA devices	
Integrated RAID (IR)		14 spread across 2 volumes
	RAID 0	10 per volume
	RAID 1	2 per volume plus hot spare
	RAID 1E	10 per volume
	RAID 10	10 per volume
Environmental	Operating	Storage
	0oC to 55oC	-45°C to 105°C
	5 to 90% Non-condensing	5 to 90% Non-condensing
MTBF	>2,000,000 Hours	
Regulatory Certifications	EMC: Class B-US (CFR 47, P15B); Canada (ICES-003); Japan (V-3/02.04); Europe (EN55022/EN55024); Australia/New Zealand (AS/NZS 3548); Safety: EN60950; RoHS; WEEE	
OS Support	Microsoft Windows, Linux (SuSE , Red Hat), Solaris, VMware See <a href="http://www.lsi.com/channel/ChannelDownloads">http://www.lsi.com/channel/ChannelDownloads</a> for details on versions	
Warranty	3 years; with advanced replacement option Free technical support at <a href="http://www.lsi.com/channel/support">http://www.lsi.com/channel/support</a>	



For more information and sales office locations, please visit the LSI web sites at: [www.lsi.com](http://www.lsi.com)

**North American Headquarters**  
Milpitas, CA  
T: +1.866.574.5741 (within U.S.)  
T: +1.408.954.3108 (outside U.S.)

**LSI Europe Ltd.**  
**European Headquarters**  
United Kingdom  
T: [+44] 1344.413200

**LSI KK Headquarters**  
Tokyo, Japan  
Tel: [+81] 3.5463.7165

LSI Corporation, the LSI logo design and SANtricity are trademarks or registered trademarks of LSI Corporation. All other brand and product names may be trademarks of their respective companies.

LSI Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI; nor does the purchase, lease, or use of a product or service from LSI convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI or of third parties.

Copyright ©2012 by LSI Corporation. All rights reserved. > 0712