

BDCOM GP1704-4F Series Commercial 100M HGUs



## BDCOM GP1704-4F Series Commercial 100M HGUs

# **Product Overview**

BDCOM GP1704-4F is a new generation smart WiFi ONU with 4 100M ports for integrated multi-service networks. It is complied with the international standard ITU-T G.9844/988 and PRC Community Industry Standard *GEPON ONU in Access Technology Requirements* and China Telecom EPON Technical Requirement CTC2.0.



**BDCOM GP1704-4F Series** 

### **Product Characteristics**

### Excellent Access Capacity

It supports the PON transmission rate of downlink 2.5Gbp/ uplink 1.25Gbps. Connected with BDCOM OLTs, it can realize 1:128 splitting ratio. The covering radius of the network can reach to 20km.

#### Secure Service Carrying Ability

For ensuring the secure service carrying ability of ONU, BDCOM has developed techniques including VLAN, STP, port isolation, ACL, QoS and Broadcast Storm Control.

#### ■ High Service Control Capability

It supports DBA and Rate-Limit. It supports advanced dynamic bandwidth distribution and accurate bandwidth limit, which enables users to share 2.5Gbps bandwidth resource appropriately. It also supports QOS function, which guarantees a reliable service quality and service priority.

#### Rich OMCI Functions

It supports the standard OMCI defined by ITU-T, including configuration, alarm, performance monitoring, fault isolation and security management, and it also supports private OMIC defined by BDCOM.

#### ■ Complete Interaction Capacity

It is complied with ITU-T G.984/988 and relevant requirements for PRC Community Industry Standard *GEPON ONU in Access Technology Requirements* and China Telecom EPON



# Technical Requirement CTC2.0.

Advanced Energy-saving Technique

It supports the "GreenTouch" architecture and "Smart@CHIP".

# **Technical Parameters**

| Attributes           | BDCOM GP1704-4F                                       |
|----------------------|---|
| User trial interface | 4 fixed 10/100M BASE-T auto-adaptation RJ45 interface |
|                      | Built-in WiFi (802.11b/g/n)                           |
| PON interface        | downlink 2.5Gbps / uplink 1.25Gbps                    |
|                      | The network covering radius: 20km                     |
|                      | Type of the optical interface: SC/UPC                 |
|                      | Hi-sensible optical receiver: -27dBm                  |
|                      | Radiation power: 0.5 ~5dBm                            |
|                      | Security: ONU authentication mechanism                |
| Standards            | ITU-T G.984/G.988                                     |
|                      | PRC Community Industry Standard GEPON ONU in Access   |
|                      | Technology Requirements                               |
|                      | IEEE 802.1D, Spanning Tree                            |
|                      | IEEE 802.1Q, VLAN                                     |
|                      | IEEE 802.1w, RSTP                                     |
|                      | ITU-T Y.1291  |
| VLAN                 | Supports 64 VLANs (1~4094)                            |
|                      | Port based VLAN                                       |
|                      | IEEE 802.1Q VLAN                                      |
|                      | CTC2.0 defined VLAN                                   |
| Multicast            | IGMP-Snooping   |
|                      | CTC defined dynamic multicast                         |
|                      | MLD-Snooping  |



| WiFi                     | 802.11b/g/n   |
|--------------------------|---|
|                          | MIMO, max rate up to 300Mbps                              |
| QoS                      | Backpressure flow control (half duplex)                   |
|                          | IEEE 802.3x flow control (full duplex)                    |
|                          | Head Of Line (HOL) mechanism                              |
|                          | IEEE 802.1p, CoS  |
|                          | Four priority queues on each port                         |
|                          | WR, SP and FIFO   |
|                          | Rate limit  |
| Reliability              | Loop detect   |
|                          | Dying-Gasp  |
| Security                 | Limitation to the number of MAC addresses on the port     |
|                          | Port protection   |
|                          | Port storm control  |
| Management               | CLI, Web, SNMP and TELNET                                 |
|                          | Software upgrade through TFTP and WEB                     |
|                          | Local syslog or server syslog                             |
| Dimensions mm (W×D×H)    | 140 x 105 x 33  |
|                          | Installation: plug and play                               |
| Heat dissipation         | Supports long-time use (For instance, 24 hours);          |
|                          | The device running hot will not affect its performance or |
|                          | cause it break down.                                      |
| Environment requirements | Operating environment: 0 °C $\sim$ 45 °C ; 10% $\sim$ 85% |
|                          | non-condensation  |
|                          | Storage environment: -40 °C $\sim$ 80 °C ; 5% $\sim$ 95%  |
|                          | non-condensation  |
| Power supply             | DC12V/1A (external adaptor power supply)                  |
| Power consumption        | <8W   |
|                          |   |



# **Ordering Information**

| Model           | Description   |
|-----------------|---|
| BDCOM GP1704-4F | FTTH/O ONU, 1 GPON interface (SC/UPC), 4 FE, built-in WiFi, |
|                 | plastic hull, DC12/1A, external adaptor (RTL solution)      |

#### **For More Information**

For more information about the BDCOM GP1704-4F ONU Series, please contact your local BDCOM account representative.

#### Shanghai Baud Data Communication Co., LTD.

No.123, Juli Road, Pudong Zhangjiang High-Tech Park, Shanghai 201203, P.R.China www.bdcom.cn

Tel: +86-21-50800666



#### Copyright ©Shanghai Baud Data Communication Co., LTD. 2015. All Rights Reserved.

This document is BDCOM Public Information.

BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time without notice.