



Cisco Optics-to-Device Compatibility Matrix Results

Network Device Product Family

ASR1000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
ASR1002-HX	GLC-GE-100FX	TMG	100 Mbps	SFP	2km	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	N	IOS XE 2.1	—
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release. Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
ASR1002-HX	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release. Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
ASR1002-HX	SFP-10G-SR-X	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release. Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
ASR1002-HX	SFP-10G-LR	TMG	10 Gbps	SFP+	10Km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10Km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-LR-X	TMG	10 Gbps	SFP+	10Km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.2S	IOS XE 16.2S
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-ER-S	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-ZR	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-ZR-S	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.6.1	IOS XE 16.6.1

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-BXD-I	TMG	10 Gbps	SFP+	10Km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-BXU-I	TMG	10 Gbps	SFP+	10Km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-BX40D-I	TMG	10 Gbps	SFP+	40km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-BX40U-I	TMG	10 Gbps	SFP+	40km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-H10GB-ACU7M	TMG	10 Gbps	SFP+	7m	Preterminated cable	DAC	N/A	Cable	0 to 70C	N	IOS XE 16.2S	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-H10GB-ACU10M	TMG	10 Gbps	SFP+	10m	Preterminated cable	DAC	N/A	Cable	0 to 70C	N	IOS XE 16.2S	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC2M	TMG	10 Gbps	SFP+	2m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC7M	TMG	10 Gbps	SFP+	7m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	SFP-10G-AOC10M	TMG	10 Gbps	SFP+	10m	Preterminated cable	AOC	N/A	Cable	0 to 70C	N	IOS XE 16.6.1	—
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	DWDM-SFP10G-61.41	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	CWDM-SFP10G-XXXX	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.11.1	IOS XE 16.11.1
ASR1002-HX	GLC-TE	TMG	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C	N	IOS XE 3.15.0S	—
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX-D	TMG	1 Gbps	SFP	10Km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 2.5	IOS XE 2.5

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX-U	TMG	1 Gbps	SFP	10Km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 2.5	IOS XE 2.5
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX40-D-I	TMG	1 Gbps	SFP	40km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX40-U-I	TMG	1 Gbps	SFP	40km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX80-D-I	TMG	1 Gbps	SFP	80km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX80-U-I	TMG	1 Gbps	SFP	80km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-BX40-DA-I	TMG	1 Gbps	SFP	40km	Single-strand Fiber	SMF	LC (PC or UPC)	Optic	-40 to 85C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-EX-SMD	TMG	1 Gbps	SFP	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 3.5S	IOS XE 3.5S
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	SFP-GE-T	TMG	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C	N	IOS XE 2.1	—
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 3.4S	IOS XE 3.4S
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
ASR1002-HX	GLC-LH-SMD	TMG	1 Gbps	SFP	10Km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 3.5S	IOS XE 3.5S
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever is the latest													
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													
ASR1002-HX	GLC-ZX-SMD	TMG	1 Gbps	SFP	70km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	IOS XE 3.4S	IOS XE 3.4S
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	CWDM-SFP-XXXX	TMG	1 Gbps	SFP	100km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 2.1	IOS XE 2.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	DWDM-SFP-XXXX	TMG	1 Gbps	SFP	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 2.1	IOS XE 2.1
Network Device Notes for above line : • ASR 1002-HX supports the above mentioned SFPs from 16.2 or 'Minimum Software Release Required' whichever latest													
ASR1002-HX	DWDM-SFP10G-30.33	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.3.1	IOS XE 16.3.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													
ASR1002-HX	DWDM-SFP10G-C	TMG	10 Gbps	SFP+	80km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	IOS XE 16.7.1	IOS XE 16.7.1
Network Device Notes for above line : • ASR 1000 platform with SPA cards: Software support on the ASR 1000 modular platforms is determined by the platform on which the SPA is installed. Refer to the SPA release notes for the correct software release.													