

Cisco 100GBASE QSFP- 100G Modules

Contents

| | |
|---|----|
| Product overview | 3 |
| Features and benefits of Cisco QSFP modules | 3 |
| Technical specifications | 7 |
| Connectors and cabling | 7 |
| Warranty | 10 |
| Cisco environmental sustainability | 10 |
| Ordering information | 11 |
| Regulatory and Standards compliance | 12 |
| Cisco Capital | 13 |
| Additional information | 13 |

Product overview

The Cisco® 100GBASE Quad Small Form-Factor Pluggable (QSFP) portfolio offers customers a wide variety of high-density and low-power 100 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications. The QSFP-100G modules are our new generation of 100G transceiver modules solution based on a QSFP form factor. (See Figure 1.)



Figure 1.
QSFP-100G Optical modules

Features and benefits of Cisco QSFP modules

- Hot-swappable input/output device that plugs into a 100G Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 100GBASE interfaces where applicable
- Certified and tested on Cisco QSFP-100G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to IEEE 802.3bm

Table 1 describes the Cisco QSFP-100G portfolio.

Table 1. Cisco QSFP-100G Portfolio

| Product | Description | Connector Type |
|----------------------------------|--|--------------------|
| QSFP-100G-SR4-S | 100GBASE SR4 QSFP Transceiver, MPO, 100m over OM4 MMF | MPO-12 (12 fibers) |
| QSFP-40/100-SRBD | 100G and 40GBASE SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF | LC |
| QSFP-100G-LR4-S | 100GBASE LR4 QSFP Transceiver, LC, 10km over SMF | LC |
| QSFP-100G-ER4L-S | 100GBASE QSFP Transceiver, 25-40KM reach over SMF, Duplex LC | LC |
| QSFP-100G-FR-S | 100GBASE FR QSFP Transceiver, 2km over SMF | LC |
| QSFP-100G-CWDM4-S | 100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF | LC |
| QSFP-100G-PSM4-S | 100GBASE PSM4 QSFP Transceiver, MPO, 500m over SMF | MPO-12 (12 fibers) |
| QSFP-100G-SM-SR | 100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C | LC |
| QSFP-100G-CU (1M, 2M, 3M, 5M) | 100GBASE-CR4 Passive Copper Cable | |

| Product | Description | Connector Type |
|---|--|----------------|
| QSFP-4SFP25G-CU (1M, 2M, 3M, 5M) | 100GBASE QSFP to 4xSFP25G Passive Copper Splitter Cables | |
| QSFP-100G-AOC (1M, 2M, 3M, 5M, 7M, 10M, 15M, 20M, 25M, 30M) | 100GBASE QSFP Active Optical Cables | |

Cisco QSFP-100G-SR4-S

The Cisco 100GBASE-SR4-S QSFP Module supports link lengths of up to 70m (100m) over OM3 (OM4) Multimode Fiber with MPO connectors. It primarily enables high-bandwidth 100G optical links over 12-fiber parallel fiber terminated with MPO multifiber connectors. QSFP-100G-SR4-S supports 100GBase Ethernet rate.

Cisco QSFP-40/100G-SRBD

The Cisco QSFP 40/100 Gb dual-rate bi-directional (BiDi) transceiver is a pluggable optical transceiver with a duplex LC connector interface for short-reach data communication and interconnect applications using Multi-Mode Fiber (MMF). It offers customers a compelling solution that enables reuse of their existing 10 Gb duplex MMF infrastructure for migration to either 40 or 100 Gigabit Ethernet connectivity.

In 40-Gbps mode, the Cisco QSFP 40/100-Gbps BiDi transceiver supports link lengths of 100 and 150 meters on laser-optimized OM3 and OM4 multimode fibers, respectively. In 100-Gbps mode, it supports 70 and 100 meters on OM3 and OM4, respectively.

Each Cisco QSFP 40/100-Gbps BiDi transceiver consists of two transmit and receive channels in the 832-918 nanometer wavelength range, enabling an aggregated 40 or 100-Gbps link over a two-strand multimode fiber connection.

Table 2. Link loss budget for QSFP-40/100-SRBD

| Mode | MMF Type | Reach (meters) | Total Loss Budget (dB) | BER |
|------|----------|----------------|------------------------|----------|
| 40G | OM3 | 100 | 1.9* | 1e-15*** |
| | OM4 | 150 | 1.5** | 1e-12 |
| 100G | OM3 | 70 | 1.9* | 1e-12 |
| | OM4 | 100 | 1.9* | 1e-12 |

* Includes 1.5dB connector loss

** Includes 1.0dB connector loss

*** In 40G mode, QSFP-40/100-SRBD has 0.7 decibel incremental margin (in addition to 1.9 decibel total loss budget shown in the table), which can be allocated to connector losses in the link for OM3 fiber for applications when a link BER of 1E-12 is sufficient. Cisco recommends that this margin be allocated to connector losses. Care should be taken to not exceed 120 meters in fiber link distance with the OM3 fiber

Cisco QSFP-100G-LR4-S

The Cisco QSFP100 LR4 Module supports link lengths of up to 10km over a standard pair of G.652 single-mode fiber with duplex LC connectors. It complies with the IEEE 100GBASE-LR4 specification, which does not employ the use of FEC. QSFP-100G-LR4-S supports 100GBase Ethernet rate.

Cisco QSFP-100G-ER4L-S

The Cisco QSFP100 ER4-Lite supports link lengths of up to 40km over a standard pair of G.652 single-mode fiber with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. Full 40km reach requires the use of FEC on the host platform. Without FEC, the reach is 30km. The QSFP100 ER4-Lite provides backward compatibility with Cisco's CPAK ER4-Lite, whose reach is up to 25km, and with IEEE 100GBASE-ER4 standardized transceivers, such as Cisco's CFP 100G ER4, up to 30km. It also interoperates with Cisco's QSFP100 and CPAK IEEE 100GBASE-LR4 modules up to 10km.

Table 3. Interoperability matrix for QSFP-100G-ER4L-S

| Interoperability matrix | QSFP-100G-ER4L-S with host FEC | CFP-100G-ER4 CFP2-100G-ER4 (IEEE 100GBASE-ER4) | QSFP-100G-ER4L-S (no FEC) | CPAK-100G-ER4L | CPAK-100G-LR4 QSFP-100G-LR4-S |
|--|--------------------------------|--|---------------------------|----------------|----------------------------------|
| QSFP-100G-ER4L-S with host FEC | 40km | | | | |
| CFP-100G-ER4 CFP2-100G-ER4 (IEEE 100GBASE-ER4) | x | 40km | | | |
| QSFP-100G-ER4L-S (no FEC) | x | 30km | 30km | | |
| CPAK-100G-ER4L ** | x | 25km | 25km* | 25km | |
| CPAK-100G-LR4 QSFP-100G-LR4-S | x | 10km | 10km | 10km | 10km |

* Maximum connector insertion loss 1.5dB

** QSFP-100G-ER4L-S interoperating with CPAK-100G-ER4L is considered an engineered link

Cisco QSFP-100G-FR-S

The Cisco QSFP-100G-FR-S Module supports link lengths of up to 2 km over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over a single wavelength using onboard PAM4 modulation and FEC. QSFP-100G-FR-S can also be used in applications meant for IEEE 100GBASE-DR, such as interoperability with IEEE 400GBASE-DR4 via fiber break-out cables.

Cisco QSFP-100G-CWDM4-S

The Cisco QSFP-100G-CWDM4-S Module supports link lengths of up to 2 km over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device.

Cisco QSFP-100G-PSM4-S

The Cisco QSFP-100G-PSM4-S Module supports link lengths of up to 500 meters over SMF with MPO connectors. The 100 Gigabit Ethernet signal is carried over 12-fiber parallel fiber terminated with MPO multifiber connectors.

Cisco QSFP-100G-SM-SR

The Cisco QSFP-100G-SM-SR QSFP module supports link lengths of up to 2 kilometers over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. The operating temperature range is from +10 to +60°C with an optical link budget of 4.2 decibels. This 4.2-decibel link budget offers the ability to support the loss from patch panels in the link in a data center environment. QSFP 100G SM-SR is interoperable with QSFP-100G-CWDM4-S.

Cisco QSFP-4SFP25G-CUxM

Cisco QSFP-100G to four SFP-25G copper direct-attach breakout cables (Figure 2) are suitable for very short links and offer a cost-effective way to connect within racks and across adjacent racks. These breakout cables connect to a 100G QSFP port of a Cisco switch on one end and to four 25G SFP ports of a Cisco switch/server on the other end. Cisco currently offers passive cables in lengths of x=1, 2, 3 and 5 meters.



Figure 2.
QSFP-4SFP25G-CUxM cables

Cisco QSFP-100G-CUxM

Cisco QSFP to QSFP copper direct-attach 100GBASE-CR4 cables (Figure 3) are suitable for very short links and offer a cost-effective way to establish a 100-Gigabit link between QSFP-100G ports of Cisco switches within racks and across adjacent racks. Cisco currently offers passive copper cables in lengths of x=1, 2, 3 and 5 meters.



Figure 3.
QSFP-100G-CU1M cables

Cisco QSFP-100G-AOCxM

Cisco QSFP-100G to QSFP-100G AOC cables (Figure 4) are suitable for short distances and offer a flexible way to connect within racks and across racks. Active optical cables are much thinner and lighter than copper cables, which makes cable management easier. AOCs enable efficient system airflow, which is critical in high-density racks. Cisco currently offers active optical cables in lengths of x=1, 2, 3, 5, 7, 10, 15, 20, 25, and 30 meters.



Figure 4.
QSFP-100G-AOC3M cables

Technical specifications

Platform support

Cisco QSFP modules are supported on Cisco switches and routers. For more details, refer to the [Cisco 100 Gigabit Ethernet Transceiver Modules Compatibility Matrix](#).

Connectors and cabling

Refer to Table 4 for connector type information and cabling specifications for each QSFP product.

Note: Except for QSFP-100G-PSM4-S, only connections with patch cords with PC or Ultra-Physical Contact (UPC) connectors are supported. QSFP-100G-PSM4-S requires patch cords with Angled Physical Contact (APC) MPO connectors. All cables and cable assemblies used must be compliant with the standards specified in the standards section of this data sheet.

Table 4. QSFP Port cabling specifications

| Cisco QSFP | Nominal Wavelength (nm) | Cable Type | Core Size (Microns) | Modal Bandwidth (MHz*km) ^{*1} | Cable Distance | Power Consumption (W) | Pull Tab Color |
|------------------|-------------------------|------------|---------------------|--|----------------|-----------------------|----------------|
| QSFP-100G-SR4-S | 850 | MMF | 50.0 | 2000 (OM3) | 70m | 3.5 | Beige |
| | | | 50.0 | 4700 (OM4) | 100m | | |
| QSFP-40/100-SRBD | 855, 908 | MMF | 50.0 | 2000 (OM3) | 70m | 3.5 | Gray |
| | | | 50.0 | 4700 (OM4) | 100m | | |
| QSFP-100G-LR4-S | 1295, 1300, 1304, 1309 | SMF | G.652 | - | 10km | 4.0 | Blue |

| Cisco QSFP | Nominal Wavelength (nm) | Cable Type | Core Size (Microns) | Modal Bandwidth (MHz*km)**1 | Cable Distance | Power Consumption (W) | Pull Tab Color |
|-------------------|-------------------------|-------------------------------------|-------------------------------|-----------------------------|---|-----------------------|----------------|
| QSFP-100G-ER4L-S | 1295, 1300, 1304, 1309 | SMF | G.652 | - | 40km (with host FEC) 30km (without host FEC) | 4.5 | Red |
| QSFP-100G-FR-S | 1310 | SMF | G.652 | - | 2km | 4.3 | Green |
| QSFP-100G-CWDM4-S | 1271, 1291, 1311, 1331 | SMF | G.652 | - | 2km | 3.5 | Green |
| QSFP-100G-PSM4-S | 1310 | SMF | G.652 | - | 500m | 3.5 | Orange |
| QSFP-100G-SM-SR | 1271, 1291, 1311, 1331 | SMF | G.652 | - | 2km | 3.5 | Green |
| QSFP-100G-CU1M | - | Direct-attach copper cable assembly | - | - | 1m | 1.5 | Beige |
| QSFP-100G-CU2M | - | | - | - | 2m | | Brown |
| QSFP-100G-CU3M | - | | - | - | 3m | | Orange |
| QSFP-100G-CU5M | - | | - | - | 5m | | Gray |
| QSFP-4SFP25G-CU1M | - | | - | - | 1m | | Beige |
| QSFP-4SFP25G-CU2M | - | | - | - | 2m | | Brown |
| QSFP-4SFP25G-CU3M | - | | - | - | 3m | | Orange |
| QSFP-4SFP25G-CU5M | - | | - | - | 5m | | Gray |
| QSFP-100G-AOC1M | - | | Active optical cable assembly | - | - | | 1m |
| QSFP-100G-AOC2M | - | - | | - | 2m | Brown | |
| QSFP-100G-AOC3M | - | - | | - | 3m | Orange | |
| QSFP-100G-AOC5M | - | - | | - | 5m | Gray | |
| QSFP-100G-AOC7M | - | - | | - | 7m | Blue | |
| QSFP-100G-AOC10M | - | - | | - | 10m | Red | |
| QSFP-100G-AOC15M | - | - | | - | 15m | Black | |
| QSFP-100G-AOC20M | - | - | | - | 20m | Green | |
| QSFP-100G-AOC25M | - | - | | - | 25m | Green | |
| QSFP-100G-AOC30M | - | - | - | 30m | Green | | |

**1 Specified at transmission wavelength. For QSFP-40/100-SRBD, Modal Bandwidth is specified at 850nm

Table 5 shows the key optical characteristics for the Cisco QSFP modules.

Table 5. Optical characteristics

| Product | Descriptions | Transmit Power (dBm) per lane ^{*2} | | Receive Power (dBm) per lane ^{*2*3} | | Transmit and Receive Wavelength (nm) |
|--------------------------------------|--|---|-----------------------|--|---|--------------------------------------|
| | | Maximum | Minimum | Maximum | Minimum | |
| QSFP-100G-SR4-S | 100GBASE SR4 QSFP Transceiver, MPO, 100m over OM4 MMF | +2.4 | -8.4 | +2.4 | -10.3 | 840 to 860 |
| QSFP-40/100G-SRBD | 100G and 40GBASE SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF | +4 (100G) +5 (40G) | -6 (100G) -4 (40G) | 4 (100G) 5 (40G) | -7.9 (100G) -6 (40G) | 855, 908 |
| QSFP-100G-LR4-S | 100GBASE LR4 QSFP Transceiver, LC, 10km over SMF | +4.5 | -4.3 | 4.5 | -10.6 | Four lanes: 1295, 1300, 1304, 1309 |
| QSFP-100G-ER4L-S^{*4} | 100GBASE QSFP Transceiver, 25-40KM reach over SMF, Duplex LC | +6.5 ^{*5} | -2.5 ^{*5} | -3.5 ^{*5} | -20.5 ^{*5} (with FEC) -17 ^{*5} (without FEC) | Four lanes: 1295, 1300, 1304, 1309 |
| QSFP-100G-FR-S | 100GBASE FR QSFP Transceiver, 2km over SMF | 4 | -2.4 | 4.5 | -6.4 | 1310 |
| QSFP-100G-CWDM4-S | 100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF | +2.5 | -6.5 | +2.5 | -11.5 | Four lanes: 1271, 1291, 1311, 1331 |
| QSFP-100G-PSM4-S | 100GBASE PSM4 QSFP Transceiver, MPO, 500m over SMF | +2.0 | -9.4 | +2 | -12.66 | 1295 to 1325 |
| QSFP-100G-SM-SR | 100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C | +2.5 | -6.9 | +2.5 | -11.1 | Four lanes: 1271, 1291, 1311, 1331 |

^{*2} Transmitter and receiver power is average optical power, unless specified

^{*3} Optical power at RX is informative only. A received power within this range is required but does not ensure operation

^{*4} Minimum channel insertion loss is 6.4dB for QSFP-100G-ER4L-S

^{*5} V01 of QSFP-100G-ER4L-S allows Tx Power range with +4.5 (Max) to -2.9 (Min) and Rx Power range with -4.9 (Max) to -19.9 (Min)

Dimensions

Maximum outer dimensions for the QSFP connector module are (H x W x D) 13.5 x 18.4 x 72.4 mm.

Cisco QSFP connector modules typically weigh 100 grams or less.

Environmental conditions

Operating temperature range:

- Commercial temperature range: 0 to 70° C (32 to 158° F). Exceptions are
 - QSFP-100G-SM-SR: +10 to 60° C (50 to 140° F)
 - QSFP-40/100-SRBD:
 - 100G: +10C to +60C
 - 40G: +10C to +70C
- Storage temperature range: -40 to 85° C (-40 to 185° F)

Warranty

- Standard warranty: 90 days

Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

| Sustainability topic | Reference |
|--|---------------------------------|
| Information on product material content laws and regulations | Materials |
| Information on electronic waste laws and regulations, including products, batteries, and packaging | WEEE compliance |

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Ordering information

Table 6 provides the ordering information for Cisco QSFP 100G modules and related cables.

Table 6. Ordering information

| Description | Product Number |
|--|-------------------|
| QSFP Optics Modules | |
| Cisco 100GBASE-SR4 QSFP Transceiver, MPO-12, 100m over OM4 MMF | QSFP-100G-SR4-S |
| Cisco 100G and 40GBASE SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF | QSFP-40/100-SRBD |
| Cisco 100GBASE-LR4 QSFP Transceiver, LC, 10km over SMF | QSFP-100G-LR4-S |
| Cisco 100GBASE QSFP Transceiver, 40KM reach over SMF, Duplex LC | QSFP-100G-ER4L-S |
| 100GBASE FR QSFP Transceiver, 2km over SMF | QSFP-100G-FR-S |
| Cisco 100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF | QSFP-100G-CWDM4-S |
| Cisco 100GBASE PSM4 QSFP Transceiver, MPO-12, 500m over SMF | QSFP-100G-PSM4-S |
| Cisco 100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C | QSFP-100G-SM-SR |
| QSFP Direct-Attach Copper Modules | |
| Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 1-meter | QSFP-100G-CU1M |
| Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 2-meter | QSFP-100G-CU2M |
| Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 3-meter | QSFP-100G-CU3M |
| Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 5-meter | QSFP-100G-CU5M |
| Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 1-meter | QSFP-4SFP25G-CU1M |
| Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 2-meter | QSFP-4SFP25G-CU2M |
| Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 3-meter | QSFP-4SFP25G-CU3M |
| Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 5-meter | QSFP-4SFP25G-CU5M |
| Cisco 100GBase QSFP Active Optical Cable, 1-meter | QSFP-100G-AOC1M |
| Cisco 100GBase QSFP Active Optical Cable, 2-meter | QSFP-100G-AOC2M |
| Cisco 100GBase QSFP Active Optical Cable, 3-meter | QSFP-100G-AOC3M |
| Cisco 100GBase QSFP Active Optical Cable, 5-meter | QSFP-100G-AOC5M |
| Cisco 100GBase QSFP Active Optical Cable, 7-meter | QSFP-100G-AOC7M |
| Cisco 100GBase QSFP Active Optical Cable, 10-meter | QSFP-100G-AOC10M |

| Description | Product Number |
|--|------------------|
| Cisco 100GBase QSFP Active Optical Cable, 15-meter | QSFP-100G-AOC15M |
| Cisco 100GBase QSFP Active Optical Cable, 20-meter | QSFP-100G-AOC20M |
| Cisco 100GBase QSFP Active Optical Cable, 25-meter | QSFP-100G-AOC25M |
| Cisco 100GBase QSFP Active Optical Cable, 30-meter | QSFP-100G-AOC30M |

Regulatory and Standards compliance

Standards:

- SFF-8665: QSFP+ 28 Gb/s 4X Pluggable Transceiver Solution (QSFP28) - Rev 1.8 May 10, 2013
- SFF-8636: Common Management Interface - DRAFT Rev 1.9 May 12, 2014
- 802.3™ -2012 IEEE Standard for Ethernet
- IEEE 802.3ba Amendment of IEEE Std 802.3-2012
- IEEE 802.3bm Amendment of IEEE Std 802.3-2012 (D3.1, 1st August 2014)
- GR-20-CORE: Generic Requirements for Optical Fiber and Optical Fiber Cable
- GR-326-CORE: Generic Requirements for Single-Mode Optical Connectors and Jumper Assemblies
- GR-468-CORE: Generic Requirements for Optoelectronic Devices Used in Telecommunications Equipment
- GR-1435-CORE: Generic Requirements for Multifiber Optical Connectors
- RoHS 6

Safety:

- Cable jacket of QSFP copper modules is UL E116441 Compliant
- QSFP copper cables are ELV compliant

Table 7. Laser Class for the QSFP-100G Optical modules

| Product | Laser Class |
|------------------------|-------------|
| Cisco QSFP-100G-SR4-S | 1 |
| Cisco QSFP-40/100-SRBD | 1M |
| Cisco QSFP-100G-LR4-S | 1 |
| Cisco QSFP-100G-ER4L-S | 1 |
| Cisco QSFP-100G-FR-S | 1 |

| Product | Laser Class |
|-------------------------|-------------|
| Cisco QSFP-100G-CWDM4-S | 1 |
| Cisco QSFP-100G-PSM4-S | 1 |
| Cisco QSFP-100G-SM-SR | 1 |

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

Additional information

For more information about Cisco 100GBASE QSFP optics and copper modules, contact your sales representative or visit

https://www.cisco.com/en/US/products/hw/modules/ps5455/prod_module_series_home.html.

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)