



### PE2G6SFPI35

#### Six Port SFP Gigabit Ethernet PCI Express Server Adapter Intel® i350AM4 Based

##### Product Description

Silicom's Six Port SFP Gigabit Ethernet PCI Express Server adapter is PCI-Express X8 network interface card that contains six Gigabit SFP ports on a PCI-Express adapter.

Silicom's Six Port SFP Gigabit Ethernet PCI-Express Server adapter is the ideal solution for implementing multiple network segments, mission-critical high-powered networking applications and environments within high performance servers.

Silicom's Six Port SFP Gigabit Ethernet PCI Express Server adapter is based on Intel i350AM4 Quad port Gigabit Ethernet MAC+PHY and Intel i350AM2 Dual port Gigabit Ethernet MAC+PHY of Intel Controller.

The Silicom i350 support PCI-SIG Single-Root I/O virtualization and sharing specification (SR-IOV).

##### Key Features

###### Performance Features:

- 8 Transmit and 8 Receive queues per port.
- Up to 8 queues of Receive Side Scaling (RSS) minimize CPU utilization across multiple processor systems
- Support PCI-SIG Single-Root I/O virtualization Rev 1.1
  - Support for up to 8 virtual function (VFs)
  - Partial replication of PCI Configuration space
- Support for 8 pools (single queue) of virtual machine Device Queues (VMDq) per port
- Support Direct Cache Access (DCA)
- Support Intel I/O Acceleration Technology v3.0
- TSO interleaving for reduced latency
- Minimized device I/O interrupts using MSI and MSI-X
- UDP, TCP and IP checksum offload



- UDP and TCP transmit segmentation offload (TSO). machine
- SCTP receive and transmit checksum offload
- Packet interrupt coalescing timers (packet timers) and absolute-delay interrupt timers for both transmit and receive operation
- EEE (IEEE 802.3az) for reduced power consumption during low link utilization periods

#### **SFP Gigabit Ethernet:**

- Gigabit Ethernet Adapters with SFP cage support:
- 1000Base-LX Fiber Gigabit Ethernet with 1000Base-LX SFP transceiver
- 1000Base-SX Fiber Gigabit Ethernet with 1000Base-SX SFP transceiver
- 1000Base-T (1000Mbit/s) Copper Gigabit Ethernet with 1000Base-T SFP transceiver
- Small Form Factor Pluggable (SFP) Cage for SFP LC connectors
- Optional SGMII mode (future support)

#### **Common Key features:**

- Support PCI Express Base Specification 2.1 (5 GTs)
- High performance, reliability, and low power use in Intel i350 Quad integrated MAC + PHY and SERDES chip Controllers
- Ultra deep, packet buffer per channel lowers CPU utilization
- Hardware acceleration that can offload tasks from the host processor. The Controllers can offload TCP/UDP/IP checksum calculations and TCP segmentation
- Server class reliability, availability and performance features:
- Link Aggregation and Load Balancing
- Priority queuing – 802.1p layer 2 priority encoding
- Virtual LANs –802.1q VLAN tagging
- Jumbo Frame (9.5KB)
- 802.x flow control
- Multicast/ broadcast Packet replication
- Supports Vital Product Data (VPD)
- LEDs indicators for link/Activity status

## Technical Specifications

### SFP Gigabit Ethernet Technical Specifications (SFP) Adapters:

<b>SFP (Small Form Factor Pluggable) supports:</b>	1 Gbit SERDES interfaces supports 1000Base-X in order to connect with SFP to 1000Base-SX / 1000Base-LX / 1000Base-T SFP transceivers.
<b>IEEE Standard / Network topology: with 1000Base-T SFP</b>	Gigabit Ethernet (1000Mbit/s only), 1000Base-T
<b>IEEE Standard / Network topology: with 1000Base-SX SFP</b>	Fiber Gigabit Ethernet, 1000Base-SX (850nm)

### Operating Systems Support

<b>Operating system support:</b>	Linux Windows FreeBSD VMware
----------------------------------	---------------------------------------

### General Technical Specifications

<b>Interface Standard:</b>	PCI-Express Base Specification Revision 2.1 (5 GTs)
<b>Board Size:</b>	Standard height short add-in card: 167.64mm x 111.15mm (6.6"X 4.376")
<b>PCI Express Card Type:</b>	X8 Lane / Gen2 5GTps
<b>PCI Express Voltage:</b>	+12V +/- 8%
<b>PCI Connector:</b>	Gold Finger: X8
<b>Controller:</b>	Intel i350AM4 and Intel i350AM2
<b>Weight:</b>	210 gram (7.4 oz)
<b>Power Consumption:</b>	12W, 1 A at 12V: Typical all ports operate at 1000 BASE-LX 11.4 W, 0.95 A at 12V: No links in all ports operate with LX transceivers 10.44 W, 0.87 A at 12V: Typical all ports operate at 1000 BASE-SX 9.84 W, 0.82 A at 12V: No links in all ports operate with SX transceivers 15.24 W, 1.27 A at 12V: Typical all ports operate at 1000 BASE-T 8.4 W, 0.7 A at 12V: No links in all ports operate at 1000 BASE-T 7.08 W, 0.59 A at 12V: Without transceivers

<b>Holder:</b>	Metal Bracket: Full Height
<b>Operating Humidity:</b>	0%–90%, non-condensing
<b>Operating Temperature:</b>	0°C – 45°C (32°F – 113°F)
<b>Storage:</b>	-40°C–65°C (-40°F–149°F)
<b>EMC Certifications:</b>	<p>FCC Part 15, Subpart B Class A</p> <p>Conducted Emissions</p> <p>Radiated Emissions</p> <p>CE EN 55022: 1998 Class A Amendments A1: 2000; A2: 2003</p> <p>Conducted Emissions</p> <p>Radiated Emissions</p> <p>CE EN 55024: 1998 Amendments A1: 2000; A2: 2003</p> <p>Immunity for ITE Amendment A1: 2001</p> <p>CE EN 61000-3-2 2000, Class A</p> <p>Harmonic Current Emissions</p> <p>CE EN 61000 3-3 1995, Amendment A1: 2001</p> <p>Voltage Fluctuations and Flicker</p> <p>CE IEC 6100-4-2: 1995</p> <p>ESD Air Discharge 8kV. Contact Discharge 4kV</p> <p>CE IEC 6100-4-3:1995</p> <p>Radiated Immunity (80-1000Mhz), 3V/m 80% A.M. by 1kHz</p> <p>CE IEC 6100-4-4:1995</p> <p>EFT/B: Immunity to electrical fast transients 1kV Power Leads, 0.5Kv Signals Leads</p> <p>CE IEC 6100-4-5:1995</p> <p>Immunity to conductive surges COM Mode; 2kV, Dif. Mode 1kV</p> <p>CE IEC 6100-4-6:1996</p> <p>Conducted immunity (0.15-80 MHz) 3VRMS 80% A.M. By 1kHz</p> <p>CE IEC 6100-4-11:1994</p> <p>Voltage Dips and Short Interruptions</p> <p>V reduc &gt;95%, 30% &gt;95% Duration 0.5per, 25per, 250per</p>
<b>MTBF:</b>	<p>105 (Years)</p> <p>*According to Telcordia SR-332 Issue 1</p> <p>Environmental condition – GB (Ground, Fixed, Controlled). Ambient temperature – 25°C.</p> <p>Temperature rise of 15°C above the system ambient temperature was assumed for the cards components</p>

LEDs	
<b>LEDs:</b>	(2) LEDs per port Link/Act LED : Turns on link (Green), Blinks on activity (Green) Link Speed LED: Turns on Yellow 1G Link. Turns on Green 100M Link (optional for SGMII mode)
<b>LEDs location:</b>	LEDs are located on the PCB, visible via holes in the metal bracket. Each Green Link/Act and Bi-color Link Speed LEDs are located above their own SFP connector port by light pipes
<b>Connectors:</b>	Small Form Factor Pluggable (SFP) Cage

### Order Information

P/N	Description	Notes
<b>PE2G6SFPi35-R</b>	Six Port SFP Gigabit Ethernet PCI Express Server Adapter	X8, PCI Express Gen2, Based on Intel i350, standard height, short PCI

-R: RoHS Compliant / Lead free adapter

1V2