



BDCOM

BDCOM ONU Series — P1504C1

BDCOM P1504C1

Product Overview

BDCOM P1504C1 is a new generation smart ONU oriented for integrated multi-service networks. It is complied with IEEE802.3ah and relevant requirements for *EPON ONU regulated in Technical Requirements of YD/T 1475-2006—Ethernet-Based EPON and China Telecom EPON Technical Requirement 2.1/3.0*. BDCOM P1504C1 can be well connected with OLTs from the mainstream manufacturers.



P1504C1

Main Characteristics

■ High Access Capacity

It supports the symmetric uplink/downlink 1Gbps PON transmission rate. Connected with BDCOM OLTs, it can realize 1:64 splitting ratio. The network covering radius can reach to 20km. The transmission distance can expand to 80km if combining the ONU with PON relay.

■ Secure Service Carrying Ability

For ensuring the secure service carrying ability of ONU, BDCOM has developed techniques including VLAN, STP, port isolation, ACL, QoS and Broadcast Storm Control.

■ High Service Control Capability

It supports functions of DBA and Rate-Limit. It supports advanced dynamic bandwidth distribution and accurate bandwidth limit, which enables users to appropriately share 1Gbps bandwidth

resource. It also supports QOS function, which guarantees a reliable service quality and service priority.

■ Rich OAM Functions

It supports standard OAM and expanded OAM defined by Chinese telecom CTC2.1/3.0, including configuration, alarm, performance monitoring, fault isolation and security management, and it also supports private OAM defined by BDCOM.

■ Complete Interaction Capacity

It is complied with IEEE802.3ah and relevant requirements for EPON ONU regulated in Technical Requirements of YD/T 1475-2006—Ethernet-Based EPON and China Telecom EPON Technical Requirement 2.1/3.0.

■ Advanced Energy-saving Technique

It supports the “GreenTouch” architecture and “Smart@CHIP”.

Technical Parameters

Attributes	P1504C1
User trial interface	4 fixed 10/100/1000M BASE-T auto-adaptation RJ45 interfaces
PON interface	The symmetric uplink/downlink 1Gbps PON transmission rate The network covering radius: 20km Type of the optical interface: SC/PC Hi-sensible optical receiver: $\geq -26\text{dBm}$ Radiation power: 0-4dBm
Dimensions mm (W×D×H)	132 x 100 x 28
	Installation: Plug and play
Environment requirements	Operating environment: 0 °C ~ 50 °C ; 10% ~ 85% non-condensation
	Storage environment: -40°C ~ 80°C; 5% ~ 95% non-condensation
Power supply	DC12V/1A adaptor power supply
Power consumption	<10W
Hull	Plastic

For More Information

For more information about the BDCOM P1504C1, please contact your local BDCOM account representative.

Shanghai Baud Data Communication co., LTD.

No.123, Juli Road,
 Pudong Zhangjiang High-Tech Park,
 Shanghai 201203, P.R.China
 www.bdc.com.cn
 Tel:+86-21-50800666

Copyright ©Shanghai Baud Data Communication co., LTD. 2014. All rights reserved.

This document is BDCOM Public Information.

BDCOM reserves the right to alter, update and otherwise change the information contained in the datasheet from time to time without notice.