

# Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards

## Product Overview

Remove bandwidth bottlenecks from increased video-on-demand (VoD), IPTV, point-to-point video, Internet video, and cloud services traffic with the Cisco® ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards (Figure 1). These powerful line cards deliver an industry-leading two 100 Gigabit Ethernet ports to any slot of a Cisco ASR 9000 Series Aggregation Services Router. Large 10 Gigabit Ethernet link aggregation bundles can now be replaced by a single 100 Gigabit Ethernet port to simplify network designs. These line cards deliver economical, scalable, highly available, line-rate Ethernet and IP/Multiprotocol Label Switching (MPLS) edge services. Both Cisco ASR 9000 Series line cards and Cisco ASR 9000 Series Routers are designed to provide the fundamental infrastructure for scalable Carrier Ethernet and IP/MPLS networks, to promote profitable business, residential, and mobile services.

**Figure 1.** Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Card



## Features and Benefits

The Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards are fully compatible with all Cisco ASR 9000 Series chassis, route switch processors (RSPs), and line cards. No hardware upgrade to the chassis or cooling system is required. Total bandwidth is dependent on the number and type of RSPs installed. The Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards are also fully compatible with the 22-slot Cisco ASR 9922 chassis.

Each line card provides simultaneous support for both Layer 2 and Layer 3 services and features, helping operators qualify and stock a single line card that can be deployed in any combination of Layer 2 and Layer 3 applications, thereby reducing capital expenditures (CapEx) and operating expenses (OpEx), as well as reducing the time required to develop and deploy new services. The Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet line cards provide significant for Layer 2 and Layer 3 service density and scale, allowing operators to offer predictable, managed transport services while optimizing the use of network assets.

The line cards, with their synchronization circuitry and dedicated backplane timing traces for accessing the RSP's Stratum-3 subsystem, provide standards-based line-interface functions for delivering and deriving transport-class network timing, allowing support of network-synchronized services and applications such as mobile backhaul and time-division multiplexing (TDM) migration. Coupled with the proper RSP, the line cards can also be used for applications requiring IEEE 1588v2 synchronization services.

Recognizing that real-time media dominate next-generation services, Cisco has integrated media-monitoring technology into the Cisco ASR 9000 Series Ethernet line cards. This multimedia technology allows real-time monitoring and statistics collection of real-time video and voice flows, facilitating proactive maintenance and management of today's comprehensive media services.

The Cisco ASR 9000 Series can extend 100 Gigabit Ethernet transport over an IP over dense wave-division multiplexing (IPoDWDM) network when used with the Cisco ONS 15454 Multiservice Transport Platform (MSTP). Distances of up to 2000 km can be achieved while using the optical protection capabilities of the DWDM network.

Table 1 lists the features and benefits of the Cisco ASR 9000 Series line cards. Specific feature and scale support is hardware and software dependent.

**Table 1.** Features and Benefits of Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards

Feature	Benefit
<b>Interface Support</b>	
<b>C Form-Factor Pluggable (CFP) interfaces</b>	Provide the capacity to mix and match 100 Gigabit Ethernet interface types across a single line card. For a complete list of supported interfaces, please see the <a href="#">Cisco ASR 9000 Transceiver Modules: Line Card Support</a> data sheet.
<b>Scalable and Integrated Multiservice Support</b>	
<b>Layer 2 and Layer 3 services</b>	Combined IP, MPLS, Ethernet, Layer 2 VPN (L2VPN), and Layer 3 VPN (L3VPN) services
<b>Evolutionary Monitoring</b>	
<b>Carrier-class operations, administration, and maintenance (O&amp;M)</b>	NetFlow, IEEE 802.1ag, IEEE 802.3ah, ITU Y.1731, IP service-level agreement (IP SLA), virtual circuit connectivity verification (VCCV), ping, and traceroute
<b>Video monitoring (VidMon)</b>	Provides real-time monitoring of video flows, including issuance of an alarm upon degradation
<b>Carrier-Class OS</b>	
<b>Cisco IOS® XR Software</b>	Modular, patchable, restartable, scalable, highly available, carrier-core and edge-proven operating system
<b>T-Class Synchronization</b>	
<b>Synchronous Ethernet</b>	Derives and provides synchronization from and to Ethernet interfaces, Cisco ASR 9000 RSP, and network synchronization interfaces
<b>IEEE 1588-2008</b>	Cisco ASR 9000 Series support of the IEEE 1588-2008 protocol, providing the capability to distribute precision time and frequency across the network

## Line Card Types

The Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards are available in Service Edge Optimized and Packet Transport Optimized variants.

- Service Edge Optimized line cards are designed for customer deployments requiring enhanced quality of service (QoS).
- Packet Transport Optimized line cards are designed for network deployments where basic QoS is required.

Different line card types may be mixed within the same system.

Feature licenses are also available to turn on advanced features on the line cards, as described in the “Software Licensing” section later in this document.

## Product Specifications

Table 2 provides product specifications for the Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet line cards.

**Table 2.** Product Specifications

Description	Specification
<b>Chassis compatibility</b>	Compatible with the Cisco ASR 9000 Series 22-slot, 10-slot, and 6-slot chassis
<b>Port density</b>	2 ports of 100 Gigabit Ethernet per line card
<b>Ethernet</b>	<ul style="list-style-type: none"> <li>• 100-Gbps IEEE 802.3ba compliant</li> <li>• 100 Gigabit Ethernet PHY monitoring</li> <li>• IEEE 802.x flow control</li> <li>• Full-duplex operation</li> <li>• Per-port byte and packet counters for policy drops; oversubscription drops; cyclic redundancy check</li> <li>• (CRC) error drops; packet sizes; and unicast, multicast, and broadcast packets</li> </ul>
<b>Performance</b>	<ul style="list-style-type: none"> <li>• 100-Gbps line-rate throughput per port</li> </ul>
<b>Options</b>	Each line card is available as either a Service Edge Optimized (enhanced QoS) or Packet Transport Optimized (basic QoS) line card
<b>Reliability and availability</b>	Line card online insertion and removal (OIR) support without affecting the system
<b>Physical dimensions (H x W x D); weight</b>	14 x 1.72 x 20.5 in.; 14 lb (35.56 x 4.37 x 52.07 cm; 6.35 kg)
<b>Network Equipment Building Standards (NEBS)</b>	Cisco ASR 9000 Series Routers are designed to meet: <ul style="list-style-type: none"> <li>• SR-3580: NEBS Criteria Levels (Level 3)</li> <li>• GR-1089-CORE: NEBS EMC and Safety</li> <li>• GR-63-CORE: NEBS Physical Protection</li> </ul>
<b>Operating temperature (nominal)</b>	41 to 104°F (5 to 40°C)
<b>Operating temperature (short-term)</b>	23 to 131°F (-5 to 55°C) Note: Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year (total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period).
<b>Operating humidity (nominal) (relative humidity)</b>	10 to 85%
<b>Storage temperature</b>	-40 to 158°F (-40 to 70°C)
<b>Storage (relative humidity)</b>	5 to 95% Note: Not to exceed 0.024 kg of water per kg of dry air
<b>Operating altitude</b>	-60 to 4000m (up to 2000m conforms to IEC, EN, UL, and CSA 60950 requirements)
<b>ETSI standards</b>	Cisco ASR 9000 Series Routers are designed to meet: <ul style="list-style-type: none"> <li>• EN300 386: Telecommunications Network Equipment (EMC)</li> <li>• ETSI 300 019 Storage Class 1.1</li> <li>• ETSI 300 019 Transportation Class 2.3</li> <li>• ETSI 300 019 Stationary Use Class 3.1</li> <li>• EN55022: Information Technology Equipment (Emissions)</li> <li>• EN55024: Information Technology Equipment (Immunity)</li> <li>• EN50082-1/EN-61000-6-1: Generic Immunity Standard</li> </ul>
<b>EMC standards</b>	Cisco ASR 9000 Series Routers are designed to meet: <ul style="list-style-type: none"> <li>• FCC Class A</li> <li>• ICES 003 Class A</li> <li>• AS/NZS 3548 Class A</li> <li>• CISPR 22 (EN55022) Class A</li> <li>• VCCI Class A</li> <li>• BSMI Class A</li> <li>• IEC/EN 61000-3-2: Power Line Harmonics</li> <li>• IEC/EN 61000-3-3: Voltage Fluctuations and Flicker</li> </ul>

Description	Specification
<b>Immunity</b>	Cisco ASR 9000 Series Routers are designed to meet: <ul style="list-style-type: none"> <li>• IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8kV Contact, 15kV Air)</li> <li>• IEC/EN-61000-4-3: Radiated Immunity (10V/m)</li> <li>• IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2kV Power, 1kV Signal)</li> <li>• IEC/EN-61000-4-5: Surge AC Port (4kV CM, 2kV DM)</li> <li>• IEC/EN-61000-4-5: Signal Ports (1kV)</li> <li>• IEC/EN-61000-4-5: Surge DC Port (1kV)</li> <li>• IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10Vrms)</li> <li>• IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m)</li> <li>• IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations</li> </ul>
<b>Safety</b>	Cisco ASR 9000 Series Routers are designed to meet: <ul style="list-style-type: none"> <li>• UL/CSA/IEC/EN 60950-1</li> <li>• IEC/EN 60825 Laser Safety</li> <li>• ACA TS001</li> <li>• AS/NZS 60950</li> <li>• FDA - Code of Federal Regulations Laser Safety</li> </ul>

## Pluggable Interfaces

The Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards support the CFP pluggable interfaces listed in Table 3. Please see the [Cisco ASR 9000 Transceiver Modules: Line Card Support](#) data sheet for a complete list of supported pluggable interfaces.

**Table 3.** CFP Interfaces Supported by the Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards

Part Number	100 Gigabit Ethernet CFP Optics	Maximum Distance
<b>CFP-100G-LR4</b>	100 Gigabit Ethernet long-reach over 4 WDM lanes (LR4) optics (single-mode fiber)	10 km
<b>CFP-100G-SR10</b>	Cisco 100GBASE-SR10 CFP Module for MMF	OM3: 100m OM4: 150m
<b>CFP-100G-ER4</b>	Cisco 100GBASE-ER4 CFP Module for SMF	40 km*

\* Links longer than 30 km for the same link power budget are considered engineered links. Attenuation for such links needs to be less than the worst case specified for single-mode fiber.

## Software Licensing

### Line Card Feature Licenses

Both optimization versions of the Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards support optional per-line-card feature licenses to turn on advanced features. Layer 3 VPN licenses provide access to VPN Routing and Forwarding (VRF) instances on a per-line-card basis. They include the Infrastructure VRF license to support up to 8 VRF instances and Advanced IP licenses to support up to full-scale VRF instances. The Advanced Video license activates the inline video monitoring feature on a per-line card basis. Table 4 lists the line card feature licenses.

**Table 4.** Feature Licenses for Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards

License Part Number	Feature Description
<b>A9K-IVRF-LIC</b>	Infrastructure VRF license to enable up to 8 VRF instances per line card
<b>A9K-2X100G-AIP-SE</b>	Advanced IP license to enable full-scale VRF instances per Service Edge Optimized 2-port 100 Gigabit Ethernet line card
<b>A9K-2X100G-AIP-TR</b>	Advanced IP license to enable full-scale VRF instances per Transport Optimized 2-port 100 Gigabit Ethernet line card
<b>A9K-2X100-VID-LIC</b>	Advanced Video license to enable inline video monitoring per 2-port 100 Gigabit Ethernet line card

## System-Level Feature Licenses

Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards also support the deployment of advanced features based on Cisco ASR 9000 Series system-level licenses. The Lawful Intercept license activates lawful intercept for surveillance of packet streams that flow through Cisco ASR 9000 Series ports. The Advanced Mobile license enables Synchronous Ethernet and IEEE 1588-2008 protocols to distribute precision time and frequency across the network. Inline video monitoring on the line cards can also be activated using a system-level Advanced Video license. Table 5 lists the system licenses supported by the line cards.

**Table 5.** System-Level Feature Licenses Supported by Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards

License Part Number	Feature Description
<b>A9K-LI-LIC</b>	Lawful Intercept license to activate lawful intercept of packet streams for surveillance
<b>A9K-MOBILE-LIC</b>	Advanced Mobile license to enable Synchronous Ethernet and IEEE 1588-2008 protocols to distribute precision timing and frequency
<b>A9K-SYS-VID-LIC</b>	Advanced Video license to activate inline video monitoring for all line cards in the system

## Ordering Information

Table 6 provides ordering information for the Cisco ASR 9000 Series 2-Port 100 Gigabit Ethernet Line Cards. For software license part numbers, see the preceding Tables 4 and 5.

**Table 6.** Ordering Information

Product Description	Part Number
<b>Cisco ASR 9000 2-Port 100GE Service Edge Optimized Line Card, Requires CFP optics</b>	A9K-2X100GE-SE
<b>Cisco ASR 9000 2-Port 100GE Packet Transport Optimized Line Card, Requires CFP optics</b>	A9K-2X100GE-TR

## Downloading the Software

Visit the [Cisco Software Center](#) to download Cisco IOS Software.

## Cisco Services for the Cisco ASR 9000 Series

Through a lifecycle services approach, Cisco delivers comprehensive support to service providers to help them successfully deploy, operate, and optimize their IP Next-Generation Networks (IP NGNs). Cisco Services for the Cisco ASR 9000 Series Aggregation Services Routers provide the services and proven methodologies that help ensure service deployment that promotes substantial return on investment, operational excellence, optimal performance, and high availability. These services are delivered using leading practices, tools, processes, and lab environments developed specifically for Cisco ASR 9000 Series deployments and post-implementation support. The Cisco Services team addresses your specific requirements, mitigates risk to existing revenue-generating services, and helps accelerate time to market for new network services.

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)

---

## For More Information

For more information about Cisco Services, contact your local Cisco account representative or visit <http://www.cisco.com/go/spservices>.




---

Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)