



# Cisco Optics-to-Device Compatibility Matrix Results

## Network Device Product Family

### N5000

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
N5K-C5596UP	SFP-10G-SR	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
N5K-C5596UP	SFP-10G-SR-S	TMG	10 Gbps	SFP+	400m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
Transceiver Notes for above line : • FDDI: 26m; OM1: 33m; OM2: 82m; OM3: 300m; OM4/OM5: 400m													
N5K-C5596UP	SFP-10G-LR	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N5K-C5596UP	SFP-10G-LR-S	TMG	10 Gbps	SFP+	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.0(3)N1(1B)	NX-OS 5.0(3)N1(1B)
N5K-C5596UP	SFP-10G-ER	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N5K-C5596UP	SFP-10G-ER-S	TMG	10 Gbps	SFP+	40km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	0 to 70C	Y	NX-OS 5.1(3)N1(1)	NX-OS 5.1(3)N1(1)
N5K-C5596UP	SFP-H10GB-CU1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	DAC	N/A	Cable	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	SFP-H10GB-CU3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	DAC	N/A	Cable	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	SFP-H10GB-CU5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	DAC	N/A	Cable	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	SFP-H10GB-ACU7M	TMG	10 Gbps	SFP+	7m	Preterminated cable	DAC	N/A	Cable	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	SFP-H10GB-ACU10M	TMG	10 Gbps	SFP+	10m	Preterminated cable	DAC	N/A	Cable	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	SFP-10G-AOC1M	TMG	10 Gbps	SFP+	1m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	SFP-10G-AOC2M	TMG	10 Gbps	SFP+	2m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	SFP-10G-AOC3M	TMG	10 Gbps	SFP+	3m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	SFP-10G-AOC5M	TMG	10 Gbps	SFP+	5m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	SFP-10G-AOC7M	TMG	10 Gbps	SFP+	7m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	SFP-10G-AOC10M	TMG	10 Gbps	SFP+	10m	Preterminated cable	AOC	N/A	Cable	0 to 70C		NX-OS 7.3(0)N1(1)	—
N5K-C5596UP	FET-10G	TMG	10 Gbps	SFP+	100m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	0 to 70C		NX-OS 5.0(3)N1(1B)	—
N5K-C5596UP	GLC-T	TMG	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	0 to 70C		NX-OS 4.0(1a)N1(1)	—
Network Device Notes for above line : • Supports 1000BASE-T mode only													
N5K-C5596UP	GLC-TE	TMG	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		NX-OS 4.0(1a)N1(1)	—
Network Device Notes for above line : • Supports 1000BASE-T mode only													
N5K-C5596UP	SFP-GE-T	TMG	10/100/1000 Mbps	SFP	100m	Cat5e/6A	Copper	RJ-45	Copper	-5 to 85C		NX-OS 4.0(1a)N1(1)	—

Network Device Product ID	Transceiver Product ID	Transceiver Business Unit	Data Rate	Form Factor	Reach	Cable Type	Media	Connector Type	Transceiver Type	Case Temp	DOM Capable	Min Software Support	DOM Support
Network Device Notes for above line : • Supports 1000BASE-T mode only													
N5K-C5596UP	GLC-SX-MMD	TMG	1 Gbps	SFP	1000m	Duplex Fiber	MMF	LC (PC or UPC)	Optic	-5 to 85C	Y	NX-OS 5.1(3)N2	NX-OS 5.1(3)N2
Transceiver Notes for above line : • FDDI: 220m; OM1: 275m; OM2: 550m; OM3, OM4/OM5: 1000m													
N5K-C5596UP	GLC-LH-SMD	TMG	1 Gbps	SFP	10km	Duplex Fiber	SMF	LC (PC or UPC)	Optic	-5 to 85C	Y	NX-OS 5.1(3)N2	NX-OS 5.1(3)N2
Transceiver Notes for above line : • GLC-LH-SMD can be used on MMF with a maximum reach of 550m • LC mode-conditioning cable required for MMF applications													