

Content

| | |
|--|-------------|
| CHAPTER 1 IPV4 MULTICAST PROTOCOL..... | 1-1 |
| 1.1 COMMANDS FOR DCSCM..... | 1-1 |
| 1.1.1 access-list (Multicast Destination Control)..... | 1-1 |
| 1.1.2 access-list (Multicast Source Control) | 1-2 |
| 1.1.3 ip multicast destination-control | 1-3 |
| 1.1.4 ip multicast destination-control access-group..... | 1-3 |
| 1.1.5 ip multicast destination-control access-group (sip)..... | 1-3 |
| 1.1.6 ip multicast destination-control access-group (vmac)..... | 1-4 |
| 1.1.7 ip multicast policy..... | 1-5 |
| 1.1.8 ip multicast source-control..... | 1-5 |
| 1.1.9 ip multicast source-control access-group | 1-5 |
| 1.1.10 multicast destination-control | 1-6 |
| 1.1.11 profile-id (Multicast Destination Control Rule List)..... | 1-6 |
| 1.1.12 show ip multicast destination-control..... | 1-7 |
| 1.1.13 show ip multicast destination-control access-list | 1-8 |
| 1.1.14 show ip multicast destination-control filter-profile-list | 1-8 |
| 1.1.15 show ip multicast policy | 1-9 |
| 1.1.16 show ip multicast source-control | 1-9 |
| 1.1.17 show ip multicast source-control access-list..... | 1-9 |
| 1.2 COMMANDS FOR IGMP SNOOPING | 1-10 |
| 1.2.1 clear ip igmp snooping vlan | 1-10 |
| 1.2.2 clear ip igmp snooping vlan <1-4094> mrouter-port..... | 1-10 |
| 1.2.3 debug igmp snooping all/packet/event/timer/mfc | 1-11 |
| 1.2.4 ip igmp snooping | 1-11 |
| 1.2.5 ip igmp snooping proxy | 1-11 |
| 1.2.6 ip igmp snooping vlan | 1-12 |
| 1.2.7 ip igmp snooping vlan immediate-leave | 1-12 |
| 1.2.8 ip igmp snooping vlan <id> immediately-leave mac-based..... | 1-13 |
| 1.2.9 ip igmp snooping vlan l2-general-querier | 1-13 |
| 1.2.10 ip igmp snooping vlan l2-general-querier-source..... | 1-14 |
| 1.2.11 ip igmp snooping vlan l2-general-querier-version | 1-14 |
| 1.2.12 ip igmp snooping vlan limit | 1-14 |
| 1.2.13 ip igmp snooping vlan interface (ethernet port-channel) IFNAME | |

| | |
|--|----------------|
| Commands for Multicast Protocol | Content |
|--|----------------|

| | |
|---|------|
| limit | 1-15 |
| 1.2.14 ip igmp snooping vlan mrouter-port interface..... | 1-16 |
| 1.2.15 ip igmp snooping vlan mrouter-port learnpim..... | 1-16 |
| 1.2.16 ip igmp snooping vlan mrpt..... | 1-17 |
| 1.2.17 ip igmp snooping vlan query-interval..... | 1-17 |
| 1.2.18 ip igmp snooping vlan query-mrsp..... | 1-17 |
| 1.2.19 ip igmp snooping vlan query-robustness | 1-18 |
| 1.2.20 ip igmp snooping vlan report source-address | 1-18 |
| 1.2.21 ip igmp snooping vlan specific-query-mrsp | 1-19 |
| 1.2.22 ip igmp snooping vlan static-group..... | 1-19 |
| 1.2.23 ip igmp snooping vlan suppression-query-time | 1-20 |
| 1.2.24 show ip igmp snooping..... | 1-20 |

CHAPTER 2 IPV6 MULTICAST PROTOCOL.....2-1

| | |
|---|------------|
| 2.1 COMMANDS FOR MLD SNOOPING CONFIGURATION | 2-1 |
| 2.1.1 clear ipv6 mld snooping vlan..... | 2-1 |
| 2.1.2 clear ipv6 mld snooping vlan <1-4094> mrouter-port..... | 2-1 |
| 2.1.3 debug mld snooping all/packet/event/timer/mfc | 2-1 |
| 2.1.4 ipv6 mld snooping | 2-2 |
| 2.1.5 ipv6 mld snooping vlan | 2-2 |
| 2.1.6 ipv6 mld snooping vlan immediate-leave..... | 2-2 |
| 2.1.7 ipv6 mld snooping vlan l2-general-querier | 2-3 |
| 2.1.8 ipv6 mld snooping vlan limit..... | 2-3 |
| 2.1.9 ipv6 mld snooping vlan mrouter-port interface..... | 2-4 |
| 2.1.10 ipv6 mld snooping vlan mrouter-port learnpim6..... | 2-4 |
| 2.1.11 ipv6 mld snooping vlan mrpt | 2-5 |
| 2.1.12 ipv6 mld snooping vlan query-interval | 2-5 |
| 2.1.13 ipv6 mld snooping vlan query-mrsp | 2-5 |
| 2.1.14 ipv6 mld snooping vlan query-robustness | 2-6 |
| 2.1.15 ipv6 mld snooping vlan static-group | 2-6 |
| 2.1.16 ipv6 mld snooping vlan suppression-query-time | 2-7 |
| 2.1.17 show ipv6 mld snooping | 2-7 |

CHAPTER 3 COMMANDS FOR MULTICAST VLAN3-1

| | |
|---|------------|
| 3.1 MULTICAST-VLAN | 3-1 |
| 3.2 MULTICAST-VLAN ASSOCIATION | 3-1 |
| 3.3 MULTICAST-VLAN ASSOCIATION INTERFACE | 3-2 |

| | |
|--|----------------|
| Commands for Multicast Protocol | Content |
|--|----------------|

| | |
|---|------------|
| 3.4 SWITCHPORT ASSOCIATION MULTICAST-VLAN | 3-3 |
| CHAPTER 4 COMMANDS FOR GMRP..... | 4-1 |
| 4.1 GMRP | 4-1 |
| 4.2 GMRP VLAN..... | 4-1 |
| 4.3 GMRP ADDRESS INTERFACE | 4-1 |
| 4.4 GMRP LEAVEALL..... | 4-2 |
| 4.5 SHOW GMRP FSM INFORMATION | 4-3 |
| 4.6 SHOW GMRP LEAVEALL FSM INFORMATION | 4-3 |
| 4.7 SHOW GMRP VLAN | 4-4 |
| 4.8 SHOW GMRP PORT-MEMBER | 4-4 |
| 4.9 SHOW GMRP LEAVETIMER RUNNING-INFORMATION | 4-4 |
| 4.10 SHOW GMRP RUNNING-INFORMATION..... | 4-5 |
| 4.11 DEBUG GMRP PACKET INTERFACE | 4-5 |
| 4.12 DEBUG GMRP INTERFACE..... | 4-6 |
| 4.13 DEBUG GMRP ERROR | 4-7 |

Chapter 1 IPv4 Multicast Protocol

1.1 Commands for DCSCM

1.1.1 access-list (Multicast Destination Control)

Command: access-list <6000-7999> {{add | delete} profile-id WORD} |
 {{deny|permit} (ip) {{<source/M>}|{host-source <source-host-ip> (range
 <2-65535>)|}}|any-source} {{<destination/M>}|{host-destination
 <destination-host-ip> (range <2-255>)|}}|any-destination}}
 no access-list <6000-7999> {deny|permit} ip {{<source>
 <source-wildcard>}|{host-source <source-host-ip> {range
 <2-65535>|}}|any-source} {{<destination>
 <destination-wildcard>}|{host-destination <destination-host-ip> {range
 <2-255>|}}|any-destination}}

Function: Configure destination control multicast access-list, the “no access-list <6000-7999> {deny|permit} ip {{<source> <source-wildcard>}|{host <source-host-ip>}|any-source} {{<destination> <destination-wildcard>}|{host-destination <destination-host-ip>}|any-destination}” command deletes the access-list.

Parameter: <6000-7999>: destination control access-list number.

{add | delete}: add or delete the profile.

{deny|permit}: deny or permit.

<source/M>: multicast source address and mask length.

<source-host-ip>: multicast source host address.

<2-65535>: the range of multicast source host.

<destination/M>: multicast destination address and mask length.

<destination-host-ip>: multicast destination host address.

<2-255>: the range of multicast destination host.

Default: None

Command Mode: Global Mode

Usage Guide: ACL of Multicast destination control list item is controlled by specifical ACL number from 6000 to 7999, the command applies to configure this ACL. ACL of ip Multicast destination control only needs to configure source IP address and destination IP

address controlled (group IP address), the configuration mode is basically the same to other ACLs, and use mask length to configure address range, and also specify a host address or all address. Remarkable, “all address” is 224.0.0.0/4 according to group IP address, not 0.0.0.0/0 in other access-list. And adding or deleting the profile-id can be used to change the multicast destination control ACL.

Example:

```
Switch(config)#access-list 6000 permit ip 10.1.1.0 0.0.0.255 232.0.0.0 0.0.0.255
Switch (config)#access-list 6000 add profile-id 1
Switch(config)#

```

1.1.2 access-list (Multicast Source Control)

Command: access-list <5000-5099> {deny|permit} ip {{<source> <source-wildcard>}|{host <source-host-ip>}|any-source} {{<destination> <destination-wildcard>}|{host-destination <destination-host-ip>}|any-destination}

no access-list <5000-5099> {deny|permit} ip {{<source> <source-wildcard>}|{host <source-host-ip>}|any} {{<destination> <destination-wildcard>}|{host-destination <destination-host-ip>}|any-destination}

Function: Configure source control multicast access-list; the “no access-list <5000-5099> {deny|permit} ip {{<source> <source-wildcard>}|{host <source-host-ip>}|any-source} {{<destination> <destination-wildcard>}|{host-destination <destination-host-ip>}|any-destination}” command deletes the access-list.

Parameter: <5000-5099>: source control access-list number.

- {deny|permit}: deny or permit.
- <source>: multicast source address..
- <source-wildcard>: multicast source address wildcard character.
- <source-host-ip>: multicast source host address.
- <destination>: multicast destination address.
- <destination-wildcard>: multicast destination address wildcard character.
- <destination-host-ip>: multicast destination host address.

Default: None

Command Mode: Global Mode

Usage Guide: ACL of Multicast source control list item is controlled by specifical ACL number from 5000 to 5099, the command applies to configure this ACL. ACL of Multicast source control only needs to configure source IP address and destination IP address controlled (group IP address), the configuration mode is basically the same to other ACLs,

and use wildcard character to configure address range, and also specify a host address or all address. Remarkable, “all address” is 224.0.0.0/4 according to group IP address, not 0.0.0.0/0 in other access-list.

Example: Switch(config)#access-list 5000 permit ip 10.1.1.0 0.0.0.255 232.0.0.0 0.0.0.255

1.1.3 ip multicast destination-control

This command is not supported by the switch.

1.1.4 ip multicast destination-control access-group

Command: ip multicast destination-control access-group <6000-7999>

no ip multicast destination-control access-group <6000-7999>

Function: Configure multicast destination-control access-list used on interface, the “**no ip multicast destination-control access-group <6000-7999>**” command deletes the configuration.

Parameter: <6000-7999>: destination-control access-list number.

Default: None

Command Mode: Interface Configuration Mode

Usage Guide: The command is only working under global multicast destination-control enabled, after configuring the command, if IGMP-SPOOPING is enabled, for adding the interface to multicast group, and match configured access-list, such as matching: permit, the interface can be added, otherwise do not be added.

Example:

Switch(config)#inter e 1/4

Switch(Config-If-Ethernet 1/4)#ip multicast destination-control access-group 6000

Switch (Config-If-Ethernet1/4)#{/p}

1.1.5 ip multicast destination-control access-group

(sip)

Command: ip multicast destination-control <IPADDRESS/M> access-group <6000-7999>

no ip multicast destination-control <IPADDRESS/M> access-group <6000-7999>

Function: Configure multicast destination-control access-list used on specified net

segment, the “**no ip multicast destination-control <IPADDRESS/M> access-group <6000-7999>**” command deletes this configuration.

Parameter: <IPADDRESS/M>: IP address and mask length;
<6000-7999>: Destination control access-list number.

Default: None

Command Mode: Global Mode

Usage Guide: The command is only working under global multicast destination-control enabled, after configuring the command, if IGMP-SPOOPING or IGMP is enabled, for adding the members to multicast group. If configuring multicast destination-control on specified net segment of transmitted igmp-report, and match configured access-list, such as matching permit, the interface can be added, otherwise do not be added. If relevant group or source in show ip igmp groups detail has been established before executing the command, it needs to execute clear ip igmp groups command to clear relevant groups in Admin mode.

Example:

```
Switch(config)#ip multicast destination-control 10.1.1.0/24 access-group 6000
```

1.1.6 ip multicast destination-control access-group (vmac)

Command: **ip multicast destination-control <1-4094> <macaddr>access-group <6000-7999>**

no ip multicast destination-control <1-4094> <macaddr>access-group <6000-7999>

Function: Configure multicast destination-control access-list used on specified vlan-mac, the “**no ip multicast destination-control <1-4094> <macaddr>access-group <6000-7999>**” command deletes this configuration.

Parameter: <1-4094>: VLAN-ID;

<macaddr>: Transmitting source MAC address of IGMP-REPORT, the format is “xx-xx-xx-xx-xx-xx”;

<6000-7999>: Destination-control access-list number.

Default: None

Command Mode: Global Mode

Usage Guide: The command is only working under global multicast destination-control enabled, after configuring the command, if IGMP-SPOOPING is enabled, for adding the members to multicast group. If configuring multicast destination-control to source MAC address of transmitted igmp-report, and match configured access-list, such as matching: permit, the interface can be added, otherwise do not be added.

Example:

```
Switch(config)#ip multicast destination-control 1 00-01-03-05-07-09 access-group 6000
```

1.1.7 ip multicast policy

Command: **ip multicast policy <IPADDRESS/M> <IPADDRESS/M> cos <priority>**

no ip multicast policy <IPADDRESS/M> <IPADDRESS/M> cos

Function: Configure multicast policy, the “**no ip multicast policy <IPADDRESS/M> <IPADDRESS/M> cos**” command deletes it.

Parameter:

<IPADDRESS/M>: are multicast source address, mask length, destination address, and mask length separately.

<priority>: specified priority, range from 0 to 7

Default: None

Command Mode: Global Mode

Usage Guide: The command configuration modifies to a specified value through the switch matching priority of specified range multicast data packet, and the TOS is specified to the same value simultaneously. Carefully, the packet transmitted in UNTAG mode does not modify its priority.

Example: Switch(config)#ip multicast policy 10.1.1.0/24 225.1.1.0/24 cos 7

1.1.8 ip multicast source-control

Command: **ip multicast source-control**

no ip multicast source-control

Function: Configure to globally enable multicast source control, the “**no ip multicast source-control**” command restores global multicast source control disabled.

Parameter: None

Default: Disabled

Command Mode: Global Mode

Usage Guide: The source control access-list applies to interface with only enabling global multicast source control, and configure to disabled global multicast source control without configuring source control access-list on every interface. After configuring the command, multicast data received from every interface does not have matching multicast source control list item, and then they will be thrown away by switches, namely only multicast data matching to PERMIT can be received and forwarded.

Example: Switch(config)#ip multicast source-control

1.1.9 ip multicast source-control access-group

Command: ip multicast source-control access-group <5000-5099>

no ip multicast source-control access-group <5000-5099>

Function: Configure multicast source control access-list used on interface, the “no ip multicast source-control access-group <5000-5099>” command deletes the configuration.

Parameter: <5000-5099>: Source control access-list number.

Default: None

Command Mode: Interface Configuration Mode

Usage Guide: The command configures with only enabling global multicast source control. After that, it will match multicast data message imported from the interface according to configured access-list, such as matching: permit, the message will be received and forwarded; otherwise the message will be thrown away.

Example:

```
Switch (config)#interface ethernet1/4
```

```
Switch (Config-If-Ethernet1/4)#ip multicast source-control access-group 5000
```

```
Switch (Config-If-Ethernet1/4)#

```

```
Switch(router-msdp)#default-rpf-peer 10.0.0.1 rp-policy 10
```

1.1.10 multicast destination-control

Command: multicast destination-control

no multicast destination-control

Function: Configure to globally enable multicast destination control, the NO command is to recover and disable the multicast destination control globally.

Parameters: None.

Default: Disabled.

Command Mode: Global Configuration Mode.

Usage Guide: Only after globally enabling the multicast destination control, the other destination control configuration can take effect; the destination access list can be applied to ports, VLAN-MAC and SIP. After configuring this command, IGMP-SNOOPING and IGMP will match according to the rules mentioned above when they try to add ports after receiving IGMP-REPORT.

Example:

```
switch(config)# multicast destination-control
```

1.1.11 profile-id (Multicast Destination Control Rule

List)

Command: profile-id <1-50> {deny|permit} {{<source/M>}|{host-source

```

<source-host-ip>          (range      <2-65535>|})|any-source}
{{<destination/M>}|{host-destination    <destination-host-ip>    (range
<2-255>|})|any-destination}
no profile-id <1-50>

```

Function: Configure the destination control profile rule. The no command deletes the profile rule.

Parameters: <1-50>: profile-id.

- {deny|permit}: deny or permit.
- <source/M>: multicast source address and mask length.
- <source-host-ip>: multicast source host address.
- <2-65535>: range of multicast source host.
- <destination/M>: multicast destination address and mask length.
- <destination-host-ip>: multicast destination host address.
- <2-255>: range of multicast destination host.

Default: None.

Command Mode: Global Mode.

Usage Guide: Profile-list of Multicast destination control list item is controlled by specifical profile-id number from 1 to 50, the command applies to configure this profile to add it into the ACL for using. Multicast destination control only needs to configure source IP address and destination IP address controlled (group IP address), the configuration mode is basically the same to ACLs, and use mask length to configure address range, and also specify a host address or all address. Remarkable, “all address” is 224.0.0.0/4 according to group IP address, not 0.0.0.0/0 in other access-list.

Example:

```
Switch (config)# profile-id 1 deny ip any-source host-destination 224.1.1.2
```

1.1.12 show ip multicast destination-control

Command: show ip multicast destination-control [detail]

- show ip multicast destination-control interface <Interfacename> [detail]
- show ip multicast destination-control host-address <ipaddress> [detail]
- show ip multicast destination-control <vlan-id> <mac-address> [detail]

Function: Display multicast destination control

Parameter: detail: expresses if it display information in detail or not..

- <Interfacename>: interface name or interface aggregation name, such as Ethernet1/1, port-channel 1 or ethernet1/1.

Default: None

Command Mode: Admin Mode and Global Mode

Usage Guide: The command displays multicast destination control rules of configuration,

including detail option, and access-list information applied in detail.

Example:

```
Switch (config)#show ip multicast destination-control
ip multicast destination-control is enabled
ip multicast destination-control 11.0.0.0/8 access-group 6003
ip multicast destination-control 1 00-03-05-07-09-11 access-group 6001
multicast destination-control access-group 6000 used on interface Ethernet1/1
switch(config)#

```

1.1.13 show ip multicast destination-control access-list

Command: **show ip multicast destination-control access-list**

show ip multicast destination-control access-list <6000-7999>

Function: Display destination control multicast access-list of configuration.

Parameter: <6000-7999>: access-list number.

Default: None

Command Mode: Admin Mode and Global Mode

Usage Guide: The command displays destination control multicast access-list of configuration.

Example:

```
Switch# sh ip multicast destination-control acc
access-list 6000 deny ip any any-destination
access-list 6000 deny ip any host-destination 224.1.1.1
access-list 6000 deny ip host 2.1.1.1 any-destination
access-list 6001 deny ip host 2.1.1.1 225.0.0.0 0.255.255.255
access-list 6002 permit ip host 2.1.1.1 225.0.0.0 0.255.255.255
access-list 6003 permit ip 2.1.1.0 0.0.0.255 225.0.0.0 0.255.255.255

```

1.1.14 show ip multicast destination-control filter-profile-list

Command: **show ip multicast destination-control filter-profile-list**

show ip multicast destination-control filter-profile-list <1-50>

Function: Show the configured destination control profile rule list.

Parameters: <1-50>: profile-id.

Default: None.

Command Mode: Admin and configuration mode.

Usage Guide: This command can show the configured destination control profile rule list.

Example:

```
Switch#show ip multicast destination-control filter-profile-list  
profile-id 1 deny ip any-source any-destination  
profile-id 2 deny ip any-source host-destination 224.1.1.1  
profile-id 3 deny ip host-source 2.1.1.1 any-destination
```

1.1.15 show ip multicast policy

Command: `show ip multicast policy`

Function: Display multicast policy of configuration

Parameter: None

Default: None

Command Mode: Admin Mode and Global Mode

Usage Guide: The command displays multicast policy of configuration

Example:

```
Switch#show ip multicast policy  
ip multicast-policy 10.1.1.0/24 225.0.0.0/8 cos 5
```

1.1.16 show ip multicast source-control

Command: `show ip multicast source-control [detail]`

`show ip multicast source-control interface <Interfacename> [detail]`

Function: Display multicast source control configuration

Parameter: detail: expresses if it displays information in detail.

<Interfacename>: interface name, such as Ethernet 1/1 or ethernet1/1.

Default: None

Command Mode: Admin Mode and Global Mode

Usage Guide: The command displays multicast source control rules of configuration, including detail option, and access-list information applied in detail.

Example:

```
Switch#show ip multicast source-control detail  
ip multicast source-control is enabled  
Interface Ethernet1/1 use multicast source control access-list 5000  
access-list 5000 permit ip 10.1.1.0 0.0.0.255 232.0.0.0 0.0.0.255  
access-list 5000 deny ip 10.1.1.0 0.0.0.255 233.0.0.0 0.255.255.255
```

1.1.17 show ip multicast source-control access-list

Command: show ip multicast source-control access-list

show ip multicast source-control access-list <5000-5099>

Function: Display source control multicast access-list of configuration

Parameter: <5000-5099>: access-list number

Default: None

Command Mode: Admin Mode and Global Mode

Usage Guide: The command displays source control multicast access-list of configuration

Example:

```
Switch#sh ip multicast source-control access-list
access-list 5000 permit ip 10.1.1.0 0.0.0.255 232.0.0.0 0.0.0.255
access-list 5000 deny ip 10.1.1.0 0.0.0.255 233.0.0.0 0.255.255.255
```

1.2 Commands for IGMP Snooping

1.2.1 clear ip igmp snooping vlan

Command: clear ip igmp snooping vlan <1-4094> groups [A.B.C.D]

Function: Delete the group record of the specific VLAN.

Parameters: <1-4094> the specific VLAN ID; A.B.C.D the specific group address.

Command Mode: Admin Configuration Mode

Usage Guide: Use show command to check the deleted group record.

Example: Delete all groups.

```
Switch#clear ip igmp snooping vlan 1 groups
```

Relative Command: show ip igmp snooping vlan <1-4094>

1.2.2 clear ip igmp snooping vlan <1-4094>

mrouter-port

Command: clear ip igmp snooping vlan <1-4094> mrouter-port [ethernet IFNAME | IFNAME]

Function: Delete the mrouter port of the specific VLAN.

Parameters: <1-4094> the specific VLAN ID; ethernet the Ethernet port name; IFNAME the port name.

Command Mode: Admin Configuration Mode

Usage Guide: Use show command to check the deleted mrouter port of the specific VLAN.

Example: Delete mrouter port in vlan 1.

Switch# clear ip igmp snooping vlan 1 mrouter-port

Relative Command: **show ip igmp snooping mrouter-port**

1.2.3 debug igmp snooping all/packet/event/timer/mfc

Command: **debug igmp snooping all/packet/event/timer/mfc**

no debug igmp snooping all/packet/event/timer/mfc

Function: Enable the IGMP Snooping switch of the switch; the “**no debug igmp snooping all/packet/event/timer/mfc**” disables the debugging switch.

Command Mode: Admin Mode

Default: IGMP Snooping debugging switch is disabled on the switch by default.

Usage Guide: The command is used for enable the IGMP Snooping debugging switch of the switch, switch IGMP data packet message can be shown with “packet” parameter, event message with “event”, timer message with “time”, downsending hardware entries message with “mfc”, and all debugging messages with “all”.

1.2.4 ip igmp snooping

Command: **ip igmp snooping**

no ip igmp snooping

Function: Enable the IGMP Snooping function; the “**no ip igmp snooping**” command disables this function.

Command mode: Global Mode

Default: IGMP Snooping is disabled by default.

Usage Guide: Use this command to enable IGMP Snooping, that is permission every VLAN config the function of IGMP snooping. The “**no ip igmp snooping**” command disables this function.

Example: Enable IGMP Snooping.

Switch(config)#ip igmp snooping

1.2.5 ip igmp snooping proxy

Command: **ip igmp snooping proxy**

no ip igmp snooping proxy

Function: Enable IGMP Snooping proxy function, the no command disables the function.

Parameter: None.

Command Mode: Global Mode

Default: Enable.

Example:

Switch(config)#no ip igmp snooping proxy

1.2.6 ip igmp snooping vlan

Command: **ip igmp snooping vlan <vlan-id>**

no ip igmp snooping vlan <vlan-id>

Function: Enable the IGMP Snooping function for the specified VLAN; the “**no ip igmp snooping vlan <vlan-id>**” command disables the IGMP Snooping function for the specified VLAN.

Parameter: **<vlan-id>** is the VLAN number.

Command mode: Global Mode

Default: IGMP Snooping is disabled by default.

Usage Guide: To configure IGMP Snooping on specified VLAN, the global IGMP Snooping should be first enabled. Disable IGMP Snooping on specified VLAN with the “**no ip igmp snooping vlan <vlan-id>**” command.

Example: Enable IGMP Snooping for VLAN 100 in Global Mode.

Switch(config)#ip igmp snooping vlan 100

1.2.7 ip igmp snooping vlan immediate-leave

Command: **ip igmp snooping vlan <vlan-id> immediate-leave**

no ip igmp snooping vlan <vlan-id> immediate-leave

Function: Enable the IGMP Snooping fast leave function for the specified VLAN; the “**no ip igmp snooping vlan <vlan-id> immediate-leave**” command disables the IGMP Snooping fast leave function.

Parameter: **<vlan-id>** is the VLAN number specified.

Command mode: Global Mode

Default: This function is disabled by default.

Usage Guide: Enable immediate-leave function of the IGMP Snooping in specified VLAN; the “no” form of this command disables the immediate-leave function of the IGMP Snooping.

Example: Enable the IGMP Snooping fast leave function for VLAN 100.

Switch(config)#ip igmp snooping vlan 100 immediate-leave

1.2.8 ip igmp snooping vlan <id> immediately-leave mac-based

Command: ip igmp snooping vlan <id> immediately-leave mac-based

no ip igmp snooping vlan <id> immediately-leave mac-based

Function: Configure this command to delete the existed igmp snooping table entries according to the source mac in leave packet when the switch which is enabled the igmp snooping function receives the leave packet. Only when the received the port, source mac and multicast group of the leave packet are the same as the port, host mac and multicast group of the existed igmp snooping table entry, the snooping table entry can be deleted. If this command is not configured, delete the existed igmp snooping table entry according to the port and multicast group of the leave packet.

Command mode: Global Mode

Default: This function is disabled by default.

Usage Guide: Configure the immediately-leave under the same vlan at the same time to make this command effective. In this time, deal with it according to the host mac of the port.

Example: Use the following configuration when delete the table entry according to the host mac of the port.

```
switch(config)#ip igmp snooping vlan 12 immediately-leave
```

```
switch(config)#ip igmp snooping vlan 12 immediately-leave mac-based
```

1.2.9 ip igmp snooping vlan l2-general-querier

Command: ip igmp snooping vlan < *vlan-id* > l2-general-querier

no ip igmp snooping vlan < *vlan-id* > l2-general-querier

Function: Set this VLAN to layer 2 general querier.

Parameter: *vlan-id*: is ID number of the VLAN, ranging is <1-4094>.

Command Mode: Global mode

Default: VLAN is not as the IGMP Snooping layer 2 general querier.

Usage Guide: It is recommended to configure a layer 2 general querier on a segment. IGMP Snooping function will be enabled by this command if not enabled on this VLAN before configuring this command, IGMP Snooping function will not be disabled when disabling the layer 2 general querier function. This command is mainly for sending general queries regularly to help switches within this segment learn mrouter ports.

Comment: There are three paths IGMP snooping learn mrouter

- 1 Port receives the IGMP query messages
- 2 Port receives multicast protocol packets, and supports DVMRP, PIM

3 Static configured port

1.2.10 ip igmp snooping vlan l2-general querier source

Command: ip igmp snooping vlan <vlanid> L2-general-query-source <A.B.C.D>

no ip igmp snooping vlan <vlanid> L2-general-query-source

Function: Configure source address of query of igmp snooping

Parameters: <vlanid>: the id of the VLAN, with limitation to <1-4094>. <A.B.C.D> is the source address of the query operation.

Command Mode: Global mode.

Default: 0.0.0.0

Usage Guide: It is not supported on Windows 2000/XP to query with the source address as 0.0.0.0. So the layer 2 query source address configuration does not function. The client will stop sending requesting datagrams after one is sent. And after a while, it can not receive multicast datagrams.

Example:

```
Switch(config)#ip igmp snooping vlan 2 L2-general-query-source 192.168.1.2
```

1.2.11 ip igmp snooping vlan

l2-general querier version

Command: ip igmp snooping vlan <vlanid> L2-general-query-version <version>

Function: Configure igmp snooping.

Parameters: **vlan-id** is the id of the VLAN, limited to <1-4094>. **version** is the version number, limited to <1-3>.

Command Mode: Global mode.

Default: version 3.

Usage Guide: When the switch is connected to V1 and V2 capable environment, and for VLAN which has source of layer 2 query configuration, the VLAN can be queried only if the version number has been specified. This command is used to query the layer 2 version number.

Example:

```
Switch(config)#ip igmp snooping vlan 2 L2-general-query-version 2
```

1.2.12 ip igmp snooping vlan limit

Command: ip igmp snooping vlan <vlan-id> limit {group <g_limit> | source <s_limit>}

no ip igmp snooping vlan <vlan-id> limit

Function: Configure the max group count of VLAN and the max source count of every group. The “no ip igmp snooping vlan <vlan-id> limit” command cancels this configuration.

Parameter: <vlan-id> is the VLAN number.

g_limit: <1-65535>, max number of groups joined.

s_limit: <1-65535>, max number of source entries in each group, consisting of include source and exclude source.

Command mode: Global Mode.

Default: Maximum 50 groups by default, with each group capable with 40 source entries.

Usage Guide: When number of joined group reaches the limit, new group requesting for joining in will be rejected for preventing hostile attacks. To use this command, IGMP snooping must be enabled on VLAN. The “no” form of this command restores the default other than set to “no limit”. For the safety considerations, this command will not be configured to “no limit”. It is recommended to use default value and if layer 3 IGMP is in operation, please make this configuration in accordance with the IGMP configuration as possible.

Example: Switch(config)#ip igmp snooping vlan 2 limit group 300

1.2.13 ip igmp snooping vlan interface (ethernet | port-channel) IFNAME limit

Command: ip igmp snooping vlan <1-4094> interface (ethernet | port-channel) IFNAME limit {group <1-65535>| source <1-65535>} strategy (replace | drop)

no ip igmp snooping vlan <1-4094> interface (ethernet | port-channel)

IFNAME limit group source strategy

Function: Configure the number of groups which are allowed joining and the maximum of the source in each group under the IGMP Snooping port. Configure the strategy when it is up to the upper limit, including “replace” and “drop”.

Parameters: *vlan-id*: VLAN ID range is <1-4094>

ethernet: Ethernet port name

ifname: Interface name

port-channel: ports aggregation

<1-65535>: The maximum number of groups allowed joining

<1-65535>: The maximum number of source table entries in each group,

including include source and exclude source.

replace: Replace the group and source information

drop: Drop the new group and source information

Command mode: Global Mode.

Default: There is no limitation as default.

Usage Guide: When the number of the groups joined under the port or the number of sources in this group exceeds the limit, it will be dealt according to the configured strategy. If it is drop, drop the new group and source information; if it is replace, find a dynamic group and source from the port to conduct deleting and replacing, and then add the new group and source information. The premise of using this command is that this VLAN is enabled IGMP Snooping function. No command configures as “no limitation”.

Example:

```
Switch(config)#ip igmp snooping vlan 2 interface ethernet 1/1 limit group 300 source 200 strategy replace
Switch(config)#

```

1.2.14 ip igmp snooping vlan mrouter-port interface

Command: `ip igmp snooping vlan <vlan-id> mrouter-port interface[<ehternet> | <port-channel>] <ifname>`

`no ip igmp snooping vlan <vlan-id> mrouter-port interface[<ehternet> | <port-channel>] <ifname>`

Function: Configure static mrouter port of VLAN. The no form of the command cancels this configuration.

Parameter: *vlan-id*: ranging between <1-4094>

ehternet: Name of Ethernet port

ifname: Name of interface

port-channel: Port aggregation

Command Mode: Global mode

Default: No static mrouter port on VLAN by default.

Usage Guide: When a port is a static mrouter port while also a dynamic mrouter port, it should be taken as a static mrouter port. Deleting static mrouter port can only be realized by the no command.

Example: Switch(config)#ip igmp snooping vlan 2 mrouter-port interface ethernet1/1

1.2.15 ip igmp snooping vlan mrouter-port learnpim

Command: `ip igmp snooping vlan <vlan-id> mrouter-port learnpim`

`no ip igmp snooping vlan <vlan-id> mrouter-port learnpim`

Function: Enable the function that the specified VLAN learns mrouter-port (according to pim packets), the no command will disable the function.

Parameter: <vlan-id>: The specified VLAN ID, ranging from 1 to 4094.

Command Mode: Global Mode

Default: Enable

Usage Guide: Enable the function that the specified VLAN learns mrouter-port (according to pim packets). After a port received pim packets, it will be set to mrouter port for implementing the automatic learning.

Example: Disable the function that vlan 100 learns mrouter-port (according to pim packets).

```
Switch(config)#no ip igmp snooping vlan 100 mrouter-port learnpim
```

1.2.16 ip igmp snooping vlan mrpt

Command: ip igmp snooping vlan <vlan-id> mrpt <value>

```
no ip igmp snooping vlan <vlan-id> mrpt
```

Function: Configure this survive time of mrouter port.

Parameter: *vlan-id*: VLAN ID, ranging between <1-4094>

value: mrouter port survive period, ranging between <1-65535>seconds

Command Mode: Global mode

Default: 255s

Usage Guide: This command validates on dynamic mrouter ports but not on mrouter port.

To use this command, IGMP Snooping of this VLAN should be enabled previously.

Example: Switch(config)#ip igmp snooping vlan 2 mrpt 100

1.2.17 ip igmp snooping vlan query-interval

Command: ip igmp snooping vlan <vlan-id> query-interval <value>

```
no ip igmp snooping vlan <vlan-id> query-interval
```

Function: Configure this query interval.

Parameter: *vlan-id*: VLAN ID, ranging between <1-4094>

value: query interval, ranging between <1-65535>seconds

Command Mode: Global mode

Default: 125s

Usage Guide: It is recommended to use the default settings. Please keep this configure in accordance with IGMP configuration as possible if layer 3 IGMP is running.

Example: Switch(config)#ip igmp snooping vlan 2 query-interval 130

1.2.18 ip igmp snooping vlan query-mrsp

Command: ip igmp snooping vlan <vlan-id> query-mrsp <value>

no ip igmp snooping vlan <vlan-id> query-mrsp

Function: Configure the maximum query response period. The “no ip igmp snooping vlan <vlan-id> query-mrsp” command restores to the default value.

Parameter: *vlan-id*: VLAN ID, ranging between <1-4094>

value: ranging between <1-25> seconds

Command Mode: Global mode

Default: 10s

Usage Guide: It is recommended to use the default settings. Please keep this configuration in accordance with IGMP configuration as possible if layer 3 IGMP is running.

Example:

Switch(config)#ip igmp snooping vlan 2 query-mrsp 18

1.2.19 ip igmp snooping vlan query-robustness

Command: ip igmp snooping vlan <vlan-id> query-robustness <value>

no ip igmp snooping vlan <vlan-id> query-robustness

Function: Configure the query robustness. The “no ip igmp snooping vlan <vlan-id> query-robustness” command restores to the default value.

Parameter: *vlan-id*: VLAN ID, ranging between <1-4094>

value: ranging between <2-10>

Command Mode: Global mode

Default: 2

Usage Guide: It is recommended to use the default settings. Please keep this configuration in accordance with IGMP configuration as possible if layer 3 IGMP is running.

Example:

Switch(config)#ip igmp snooping vlan 2 query- robustness 3

1.2.20 ip igmp snooping vlan report source-address

Command: ip igmp snooping vlan <vlan-id> report source-address <A.B.C.D>

no ip igmp snooping vlan <vlan-id> report source-address

Function: Configure forward report source-address for IGMP, the “no ip igmp snooping vlan <vlan-id> report source-address” command restores the default setting.

Parameter: *vlan-id*: VLAN ID range<1-4094>;

A.B.C.D: IP address, can be 0.0.0.0.

Command Mode: Global Mode.

Default: Disabled.

Usage Guide: Default configuration is recommended here. If IGMP snooping needs to be configured, the source address for forwarded IGMP messages can be 0.0.0.0. If it is required by the upstream that IGMP messages should use the same network address, the source address of IGMP messages should be configured to be the same with upstream.

Example:

```
Switch (config)#ip igmp snooping vlan 2 report source-address 10.1.1.1
```

1.2.21 ip igmp snooping vlan specific-query-mrsp

Command: `ip igmp snooping vlan <vlan-id> specific-query-mrsp <value>`
`no ip igmp snooping vlan <vlan-id> specific-query-mrsp`

Function: Configure the maximum query response time of the specific group or source, the no command restores the default value.

Parameters: `<vlan-id>`: the specific VLAN ID, the range from 1 to 4094.

`<value>`: the maximum query response time, unit is second, the range from 1 to 25, default value is 1.

Command Mode: Global mode

Default: Enable the function.

Usage Guide: After enable vlan snooping in global mode, input this command to configure the maximum query response time of the specific group.

Example: Configure/cancel the specific-query-mrsp of vlan3 as 2s.

```
Switch(config)#ip igmp snooping vlan 3 specific-query-mrsp 2
```

```
Switch(config)#no ip igmp snooping vlan 3 specific-query-mrsp
```

1.2.22 ip igmp snooping vlan static-group

Command: `ip igmp snooping vlan <vlan-id> static-group <A.B.C.D> [source <A.B.C.D>] interface [ethernet | port-channel] <IFNAME>`
`no ip igmp snooping vlan <vlan-id> static-group <A.B.C.D> [source <A.B.C.D>] interface [ethernet | port-channel] <IFNAME>`

Function: Configure static-group on specified port of the VLAN. The no form of the command cancels this configuration.

Parameter: `vlan-id`: ranging between <1-4094>

`A.B.C.D`: the address of group or source

`ethernet`: Name of Ethernet port

`port-channel`: Port aggregation

`ifname`: Name of interface

Command Mode: Global mode

Default: No configuration by default.

Usage Guide: When a group is a static while also a dynamic group, it should be taken as a static group. Deleting static group can only be realized by the no form of the command.

Example:

```
Switch(config)#ip igmp snooping vlan 1 static-group 224.1.1.1 source 192.168.1.1
interface ethernet 1/1
```

1.2.23 ip igmp snooping vlan suppression-query-time

Command: `ip igmp snooping vlan <vlan-id> suppression-query-time <value>`

`no ip igmp snooping vlan <vlan-id> suppression-query-time`

Function: Configure the suppression query time. The “`no ip igmp snooping vlan <vlan-id> suppression-query-time`” command restores to the default value.

Parameter: `vlan-id`: VLAN ID, ranging between <1-4094>

`value`: ranging between<1-65535> seconds

Command Mode: Global mode

Default: 255s

Usage Guide: This command can only be configured on L2 general querier. The Suppression-query-time refers to the period of suppression state in which the querier enters when receives query from the layer 3 IGMP in the segments.

Example: Switch(config)#ip igmp snooping vlan 2 suppression-query-time 270

1.2.24 show ip igmp snooping

Command: `show ip igmp snooping [vlan <vlan-id>]`

Parameter: `<vlan-id>` is the VLAN number specified for displaying IGMP Snooping messages.

Command Mode: Admin Mode

Usage Guide: If no VLAN number is specified, it will show whether global IGMP Snooping switch is on, which VLAN is configured with l2-general-querier function, and if a VLAN number is specified, detailed IGMP messages for this VLAN will be shown.

Example:

1. Show IGMP Snooping summary messages of the switch

```
Switch(config)#show ip igmp snooping
```

Global igmp snooping status: Enabled

L3 multicasting: running

Igmp snooping is turned on for vlan 1(querier)

Igmp snooping is turned on for vlan 2

| Displayed Information | Explanation |
|--|---|
| Global igmp snooping status | Whether the global igmp snooping switch on the switch is on |
| L3 multicasting | whether the layer 3 multicast protocol of the switch is running |
| Igmp snooping is turned on for vlan 1(querier) | which VLANs on the switch is enabled with igmp snooping function, whether they are l2-general-querier |

2. Display the IGMP Snooping summary messages of vlan1.

Switch#show ip igmp snooping vlan 1

Igmp snooping information for vlan 1

| | |
|--|-------------------|
| Igmp snooping L2 general querier | :Yes(COULD_QUERY) |
| Igmp snooping query-interval | :125(s) |
| Igmp snooping max reponse time | :10(s) |
| Igmp snooping robustness | :2 |
| Igmp snooping mrouter port keep-alive time | :255(s) |
| Igmp snooping query-suppression time | :255(s) |

IGMP Snooping Connect Group Membership

Note:*-All Source, (S)- Include Source, [S]-Exclude Source

| Groups | Sources | Ports | Exptime | System Level |
|-----------|---------------|-------------|----------|--------------|
| 238.1.1.1 | (192.168.0.1) | Ethernet1/8 | 00:04:14 | V2 |
| | (192.168.0.2) | Ethernet1/8 | 00:04:14 | V2 |

Igmp snooping vlan 1 mrouter port

Note:"!"-static mrouter port

!Ethernet1/2

| Displayed Information | Explanation |
|----------------------------------|--|
| Igmp snooping L2 general querier | Whether the VLAN enables l2-general-querier function and show whether the querier state is could-query or suppressed |
| Igmp snooping query-interval | Query interval of the VLAN |
| Igmp snooping max reponse | Max response time of the VLAN |

| | |
|--|--|
| time | |
| Igmp snooping robustness | IGMP Snooping robustness configured on the VLAN |
| Igmp snooping mrouter port keep-alive time | keep-alive time of dynamic mrouting of the VLAN |
| Igmp snooping query-suppression time | Suppression timeout of VLAN when as I2-general-querier |
| IGMP Snooping Connect Group Membership | Group membership of this VLAN, namely the correspondence between ports and (S,G) |
| Igmp snooping vlan 1 mrouter port | mrouting port of the VLAN, including both static and dynamic |

Chapter 2 IPv6 Multicast Protocol

2.1 Commands for MLD Snooping Configuration

2.1.1 clear ipv6 mld snooping vlan

Command: `clear ipv6 mld snooping vlan <1-4094> groups [X:X::X:X]`

Function: Delete the group record of the specific VLAN.

Parameters: <1-4094> the specific VLAN ID; X:X::X:X the specific group address.

Command Mode: Admin Configuration Mode

Usage Guide: Use show command to check the deleted group record.

Example: Delete all groups.

Switch#`clear ipv6 mld snooping vlan 1 groups`

Relative Command: `show ipv6 mld snooping vlan <1-4094>`

2.1.2 clear ipv6 mld snooping vlan <1-4094>

mrouter-port

Command: `clear ipv6 mld snooping vlan <1-4094> mrouter-port [ethernet IFNAME|IFNAME]`

Function: Delete the mrouter port of the specific VLAN.

Parameters: <1-4094> the specific VLAN ID; ethernet the Ethernet port name; IFNAME the port name.

Command Mode: Admin Configuration Mode

Usage Guide: Use show command to check the deleted group record.

Example: Delete the mrouter port in vlan 1.

Switch#`clear ipv6 mld snooping vlan 1 mrouter-port`

Relative Command: `show ipv6 mld snooping mrouter-port`

2.1.3 debug mld snooping all/packet/event/timer/mfc

Command: `debug mld snooping all/packet/event/timer/mfc`

`no debug mld snooping all/packet/event/timer/mfc`

Function: Enable the debugging of the switch MLD Snooping; the “no” form of this command disables the debugging.

Command Mode: Admin Mode

Default: The MLD Snooping Debugging of the switch is disabled by default

Usage Guide: This command is used for enabling the switch MLD Snooping debugging, which displays the MLD data packet message processed by the switch—packet, event messages—event, timer messages—timer, messages of down streamed hardware entry—mfc, all debug messages—all.

2.1.4 ipv6 mld snooping

Command: **ipv6 mld snooping**

no ipv6 mld snooping

Function: Enable the MLD Snooping function on the switch; the “**no ipv6 mld snooping**” command disables MLD Snooping.

Command Mode: Global Mode

Default: MLD Snooping disabled on the switch by default

Usage Guide: Enable global MLD Snooping on the switch, namely allow every VLAN to be configured with MLD Snooping; the “no” form of this command will disable MLD Snooping on all the VLANs as well as the global MLD snooping

Example: Enable MLD Snooping under global mode.

Switch (config)#ipv6 mld snooping

2.1.5 ipv6 mld snooping vlan

Command: **ipv6 mld snooping vlan <vlan-id>**

no ipv6 mld snooping vlan <vlan-id>

Function: Enable MLD Snooping on specified VLAN; the “no” form of this command disables MLD Snooping on specified VLAN.

Parameter: **<vlan-id>** is the id number of the VLAN, with a valid range of <1-4094>.

Command Mode: Global Mode

Default: MLD Snooping disabled on VLAN by default

Usage Guide: To configure MLD snooping on certain VLAN, the global MLD snooping should be first enabled. Disable MLD snooping on specified VLAN with the no ipv6 mld snooping vlan vid command

Example: Enable MLD snooping on VLAN 100 under global mode.

Switch (config)#ipv6 mld snooping vlan 100

2.1.6 ipv6 mld snooping vlan immediate-leave

Command: **ipv6 mld snooping vlan <vlan-id> immediate-leave**

no ipv6 mld snooping vlan <vlan-id> immediate-leave

Function: Enable immediate-leave function of the MLD protocol in specified VLAN; the “no” form of this command disables the immediate-leave function of the MLD protocol

Parameter: <vlan-id> is the id number of specified VLAN, with valid range of <1-4094>.

Command Mode: Global Mode

Default: Disabled by default

Usage Guide: Enabling the immediate-leave function of the MLD protocol will hasten the process the port leaves one multicast group, in which the specified group query of the group will not be sent and the port will be directly deleted.

Example: Enable the MLD immediate-leave function on VLAN 100.

Switch (config)#ipv6 mld snooping vlan 100 immediate-leave

2.1.7 ipv6 mld snooping vlan l2-general-querier

Command: **ipv6 mld snooping vlan <vlan-id> l2-general-querier**

no ipv6 mld snooping vlan <vlan-id> l2-general-querier

Function: Set the VLAN to Level 2 general querier.

Parameter: **vlan-id:** is the id number of the VLAN, with a valid range of <1-4094>

Command Mode: Global Mode

Default: VLAN is not a MLD Snooping L2 general querier by default.

Usage Guide: It is recommended to configure an L2 general querier on a segment. If before configure with this command, MLD snooping is not enabled on this VLAN, this command will no be executed. When disabling the L2 general querier function, MLD snooping will not be disabled along with it. Main function of this command is sending general queries periodically to help the switches within this segment learn mrouter port.

Comment: There are three ways to learn mrouter port in MLD Snooping:

1. The port which receives MLD query messages
2. The port which receives multicast protocol packets and support PIM
3. The port statically configured.

Example: Set VLAN 100 to L2 general querier.

Switch (config)# ipv6 mld snooping vlan 100 l2-general-querier

2.1.8 ipv6 mld snooping vlan limit

Command: **ipv6 mld snooping vlan <vlan-id> limit {group <g_limit> | source <s_limit>}**

no ipv6 mld snooping vlan <vlan-id> limit

Function: Configure number of groups the MLD snooping can join and the maximum number of sources in each group.

Parameter: **vlan-id:** VLAN ID, the valid range is <1-4094>

g_limit: <1-65535>, max number of groups joined

s_limit: <1-65535>, max number of source entries in each group, consisting of include source and exclude source

Command Mode: Global Mode

Default: Maximum 50 groups by default, with each group capable with 40 source entries.

Usage Guide: When number of joined group reaches the limit, new group requesting for joining in will be rejected for preventing hostile attacks. To use this command, MLD snooping must be enabled on VLAN. The “no” form of this command restores the default other than set to “no limit”. For the safety considerations, this command will not be configured to “no limit”. It is recommended to use default value and if layer 3 MLD is in operation, please make this configuration in accordance with the MLD configuration as possible.

Example: Switch(config)#ipv6 mld snooping vlan 2 limit group 300

2.1.9 ipv6 mld snooping vlan mrouter-port interface

Command: ipv6 mld snooping vlan <vlan-id> mrouter-port interface [<ethernet>|<port-channel>] <filename>
no ipv6 mld snooping vlan <vlan-id> mrouter-port interface [<ethernet>|<port-channel>] <filename>

Function: Set the static mrouter port of the VLAN; the “no” form of this command cancels the configuration.

Parameter: **vlan-id:** VLAN id, the valid range is<1-4094>

Ethernet: name of Ethernet port

Ifname: Name of interface

port-channel: port aggregate

Command Mode: Global Mode

Default: When a port is made static and dynamic mrouter port at the same time, it's the static mrouter properties is preferred. Deleting the static mrouter port can only be done with the “no” form of this command.

Example: Switch(config)#ipv6 mld snooping vlan 2 mrouter-port interface ethernet1/1

2.1.10 ipv6 mld snooping vlan mrouter-port learnpim6

Command: ipv6 mld snooping vlan <vlan-id> mrouter-port learnpim6

no ipv6 mld snooping vlan <vlan-id> mrouter-port learnpim6

Function: Enable the function that the specified VLAN learns mrouter-port (according to pimv6 packets), the no command will disable the function.

Parameter: <vlan-id>: The specified VLAN ID, ranging from 1 to 4094.

Command Mode: Global Mode

Default: Enable

Usage Guide: Enable the function that the specified VLAN learns mrouter-port (according to pimv6 packets). After a port received pimv6 packets, it will be set to mrouter port for implementing the automatic learning.

Example: Disable the function that vlan 100 learns mrouter-port (according to pimv6 packets).

```
Switch(config)#no ipv6 mld snooping vlan 100 mrouter-port learnpim6
```

2.1.11 ipv6 mld snooping vlan mrpt

Command: `ipv6 mld snooping vlan <vlan-id> mrpt <value>`

`no ipv6 mld snooping vlan <vlan-id> mrpt`

Function: Configure the keep-alive time of the mrouter port.

Parameter: *vlan-id*: VLAN ID, the valid range is <1-4094>

value: mrouter port keep-alive time with a valid range of <1-65535> secs.

Command Mode: Global Mode

Default: 255s

Usage Guide: This configuration is applicable on dynamic mrouter port, but not on static mrouter port. To use this command, MLD snooping must be enabled on the VLAN.

Example: Switch(config)#ipv6 mld snooping vlan 2 mrpt 100

2.1.12 ipv6 mld snooping vlan query-interval

Command: `ipv6 mld snooping vlan <vlan-id> query-interval <value>`

`no ipv6 mld snooping vlan <vlan-id> query-interval`

Function: Configure the query interval.

Parameter: *vlan-id*: VLAN ID, the valid range is <1-4094>

value: query interval, valid range: <1-65535>secs.

Command Mode: Global Mode

Default: 125s

Usage Guide: It is recommended to use default value and if layer 3 MLD is in operation, please make this configuration in accordance with the MLD configuration as possible.

Example:

```
Switch(config)#ipv6 mld snooping vlan 2 query-interval 130
```

2.1.13 ipv6 mld snooping vlan query-mrsp

Command: `ipv6 mld snooping vlan <vlan-id> query-mrsp <value>`

no ipv6 mld snooping vlan <vlan-id> query-mrsp

Function: Configure the maximum query response period. The “no” form of this command restores the default value.

Parameter: *vlan-id*: VLAN ID, the valid range is<1-4094>

value: the valid range is <1-25> secs .

Command Mode: Global Mode

Default: 10s

Usage Guide: It is recommended to use default value and if layer 3 MLD is in operation, please make this configuration in accordance with the MLD configuration as possible.

Example:

Switch(config)#ipv6 mld snooping vlan 2 query-mrsp 18

2.1.14 ipv6 mld snooping vlan query-robustness

Command: **ipv6 mld snooping vlan <vlan-id> query-robustness <value>**

no ipv6 mld snooping vlan <vlan-id> query-robustness

Function: Configure the query robustness; the “no” form of this command restores to the default value.

Parameter: *vlan-id*: VLAN ID, the valid range is <1-4094>

value: the valid range is <2-10>.

Command Mode: Global Mode

Default: 2

Usage Guide: It is recommended to use default value and if layer 3 MLD is in operation, please make this configuration in accordance with the MLD configuration as possible.

Example:

Switch(config)#ipv6 mld snooping vlan 2 query- robustness 3

2.1.15 ipv6 mld snooping vlan static-group

Command: **ipv6 mld snooping vlan<vlan-id> static-group <X:X::X:X> [source<X:X::X:X>] interface [ethernet | port-channel] <IFNAME>**

no ipv6 mld snooping vlan <vlan-id> static-group <X:X::X:X> [source<X:X::X:X>] interface [ethernet | port-channel] <IFNAME>

Function: Configure static-group on specified port of the VLAN. The no form of the command cancels this configuration.

Parameter: *vlan-id*: ranging between <1-4094>

X:X::X:X:The address of group or source.

ethernet: Name of Ethernet port

port-channel: Port aggregation

ifname: Name of interface

Command Mode: Global mode

Default: No configuration by default.

Usage Guide: When a group is a static while also a dynamic group, it should be taken as a static group. Deleting static group can only be realized by the no form of the command.

Example:

```
Switch(config)#ip igmp snooping vlan 1 static-group ff1e::15 source 2000::1 interface
ethernet 1/1
```

2.1.16 ipv6 mld snooping vlan suppression-query-time

Command: **ipv6 mld snooping vlan <vlan-id> suppression-query-time <value>**

no ipv6 mld snooping vlan <vlan-id> suppression-query-time

Function: Configure the suppression query time; the “no” form of this command restores the default value.

Parameter: **vlan-id:** VLAN ID, valid range: <1-4094>

value: valid range: <1-65535>secs.

Command Mode: Global Mode

Default: 255s

Usage Guide: This command can only be configured on L2 general querier. The Suppression-query-time represents the period the suppression state maintains when general querier receives queries from layer 3 MLD within the segment. To use this command, the query-intervals in different switches within the same segment must be in accordance. It is recommended to use the default value.

Example:

```
Switch(config)#ipv6 mld snooping vlan 2 suppression-query-time 270
```

2.1.17 show ipv6 mld snooping

Command: **show ipv6 mld snooping [vlan <vlan-id>]**

Parameter: **<vlan-id>** is the number of VLAN specified to display the MLD Snooping messages

Command Mode: Admin Mode

Usage Guide: If no VLAN number is specified, it will show whether the global MLD snooping is enabled and layer 3 multicast protocol is running, as well as on which VLAN the MLD Snooping is enabled and configured I2-general-querier. If a VLAN number is specified, the detailed MLD Snooping messages of this VLAN will be displayed.

Example:

1. Summary of the switch MLD snooping

```
Switch(config)#show ipv6 mld snooping
Global mld snooping status: Enabled
L3 multicasting: running
Mld snooping is turned on for vlan 1(querier)
Mld snooping is turned on for vlan 2
-----
```

| Displayed Information | Explanation |
|---|--|
| Global mld snooping status | Whether or not the global MLD Snooping is enabled on the switch |
| L3 multicasting | Whether or not the layer 3 multicast protocol is running on the switch. |
| Mld snooping is turned on for vlan 1(querier) | On which VLAN of the switch is enabled MLD Snooping, if the VLAN are l2-general-querier. |

2. Display the detailed MLD Snooping information of vlan1

```
Switch#show ipv6 mld snooping vlan 1
```

Mld snooping information for vlan 1

| | |
|---|-------------------|
| Mld snooping L2 general querier | :Yes(COULD_QUERY) |
| Mld snooping query-interval | :125(s) |
| Mld snooping max reponse time | :10(s) |
| Mld snooping robustness | :2 |
| Mld snooping mrouter port keep-alive time | :255(s) |
| Mld snooping query-suppression time | :255(s) |

MLD Snooping Connect Group Membership

Note:*-All Source, (S)- Include Source, [S]-Exclude Source

| Groups | Sources | Ports | Exptime | System Level |
|----------|-----------|-------------|----------|--------------|
| Ff1e::15 | (2000::1) | Ethernet1/8 | 00:04:14 | V2 |
| | (2000::2) | Ethernet1/8 | 00:04:14 | V2 |

Mld snooping vlan 1 mrouter port

Note:"!"-static mrouter port

!Ethernet1/2

| Displayed information | Explanation |
|---------------------------------|---|
| Mld snooping L2 general querier | whether or not l2-general-querier is enabled on VLAN, the querier display status is set to could-query or |

| | |
|---|--|
| | suppressed |
| Mld snooping query-interval | Query interval time of the VLAN |
| Mld snooping max response time | Max response time of this VLAN |
| Mld snooping robustness | Robustness configured on the VLAN |
| Mld snooping mrouter port keep-alive time | Keep-alive time of the dynamic mrouter on this VLAN |
| Mld snooping query-suppression time | timeout of the VLAN as l2-general-querier at suppressed status. |
| MLD Snooping Connect Group Membership | Group membership of the VLAN, namely the correspondence between the port and (S,G) . |
| Mld snooping vlan 1 mrouter port | Mrouter port of the VLAN, including both static and dynamic. |

Chapter 3 Commands for Multicast VLAN

3.1 multicast-vlan

Command: **multicast-vlan**

no multicast-vlan

Function: Enable multicast VLAN function on a VLAN; the “no” form of this command disables the multicast VLAN function.

Parameter: None.

Command Mode: VLAN Configuration Mode.

Default: Multicast VLAN function not enabled by default.

Usage Guide: The multicast VLAN function can not be enabled on Private VLAN. To disabling the multicast VLAN function of the VLAN, configuration of VLANs associated with the multicast VLAN should be deleted. Note that the default VLAN can not be configured with this command and only one multicast VLAN is allowed on a switch.

Examples:

```
Switch(config)#vlan 2
```

```
Switch(Config-Vlan2)# multicast-vlan
```

3.2 multicast-vlan association

Command: **multicast-vlan association <vlan-list>**

no multicast-vlan association <vlan-list>

Function: Associate several VLANs with a multicast VLAN; the “no” form of this command cancels the association relations.

Parameter: **<vlan-list>** the VLAN ID list associated with multicast VLAN. Each VLAN can only be associated with one multicast VLAN and the association will only succeed when every VLAN listed in the VLAN ID table exists.

Command Mode: VLAN Mode.

Default: The multicast VLAN is not associated with any VLAN by default.

Usage Guide: After a VLAN is associated with the multicast VLAN, when there comes the multicast order in the port of this VLAN, then the multicast data will be sent from the multicast VLAN to this port, so to reduce the data traffic. The VLAN associated with the multicast VLAN should not be a Private VLAN. A VLAN can only be associated with

another VLAN after the multicast VLAN is enabled. Only one multicast VLAN can be enabled on a switch.

Examples:

```
Switch(config)#vlan 2
```

```
Switch(Config-Vlan2)# multicast-vlan association 3, 4
```

3.3 multicast-vlan association interface

Command: **multicast-vlan association interface (ethernet | port-channel) IFNAME out-tag <tag-id>**

```
no multicast-vlan association interface (ethernet | port-channel)
```

IFNAME

Function: Associate the specified port with the multicast VLAN, so the associated ports are able to receive the multicast flow. The no command cancels the association between the ports and the multicast VLAN.

Parameter: IFNAME: The name of the ethernet port or port-channel port

tag-id: Specify vlan tag of the multicast data forwarded by the associated port, only the tag of the associated port allows the multicast VLAN, the tag-id takes effect. Its range from 1 to 4094.

Command Mode: VLAN configuration mode

Default: None.

Usage Guide:

1. ‘associated VLAN’ and ‘associated port’ of the multicast VLAN are absolute, they do not affect each other when happening the cross.
2. The port of the aggregation member cannot be associated, but the associated port is able to be added to port-group and cancelling the association.
3. The configured port type includes port-channel port or ethernet port and the port is only configured as ACCESS mode.
4. The port (it will be associated) cannot belong to the multicast VLAN, in the same way, the associated port cannot be divided in multicast VLAN.
5. When the associated port mode is set as non ACCESS mode, the mode cannot be changed.

Example: Suppose vlan2 is multicast VLAN.

```
Switch(config-vlan2)#multicast-vlan association interface ethernet 1/2
```

```
Switch(config-vlan2)#multicast-vlan association interface port-channel 2
```

```
Switch(config-vlan2)#no multicast-vlan association interface ethernet 1/2
```

```
Switch(config-vlan2)#no multicast-vlan association interface port-channel 2
```

3.4 switchport association multicast-vlan

Command: **switchport association multicast-vlan <vlan-id> out-tag <tag-id>**
no switchport association multicast-vlan <vlan-id>

Function: Associate a port with the specified multicast VLAN; the no command cancels the association.

Parameter: **<vlan-id>**: The multicast VLAN associates with the port. Each port can only be associated with one multicast VLAN, and the association will be successful only when the multicast VLAN is existent.

<tag-id>: Specify vlan tag of the multicast data forwarded by the associated port, only the tag of the associated port allows the multicast VLAN, the tag-id takes effect. Its range from 1 to 4094.

Command Mode: Port mode.

Default: The port is not associated with any multicast VLAN by default.

Usage Guide: After a port is associated with the multicast VLAN, when there comes the multicast order in the port, then the multicast data will be sent from the multicast VLAN to this port, so to reduce the data traffic. If the associated port is set as trunk port and allows the multicast VLAN, the multicast traffic with the specified vlan tag will be forwarded. The port can only be associated with the multicast VLAN after the multicast VLAN is enabled.

Example:

```
Switch(config)#vlan 2
Switch(Config-Vlan2)#multicast-vlan
Switch(config)#interface ethernet 1/1
Switch(config-if-ethernet1/1)#switchport mode trunk
Switch(config-if-ethernet1/1)#switchport association multicast-vlan 2 out-tag 5
```

Chapter 4 Commands for GMRP

4.1 gmrp

Command: gmrp

 no gmrp

Function: Enable the function of GMRP in global or port.

Command Mode: Global and Port Mode.

Default: Do not enable the function of GMRP in global or port; If the switch enables the function of GMRP in global, the function of GMRP in port is not enabled.

Usage Guide: The port can enable GMRP if the function of GMRP is not enabled in global. But this configuration will become effective only if the function of GMRP is enabled in global.

Example: Enable the function of GMRP of the switch and enable GMRP in port of 1/2.

```
Switch(config)#gmrp  
Switch(config)#interface ethernet 1/2  
Switch(Config-If-Ethernet1/2)#gmrp
```

4.2 gmrp vlan

Command: gmrp vlan <vlanlist>

 no gmrp vlan <vlanlist>

Function: Enable/disable the function of GMRP on VLAN.

Parameters: <vlanlist>:the id number of vlan.

Command Mode: Global Mode

Default: Disable the function of GMRP on VLAN.

Usage Guide: Enable the function of VLAN GMRP before using GMRP. Only if this function of vlan is enabled, GMRP will work normally.

Example: Enable the function of GMRP on vlan1-100.

```
Switch(config)#gmrp vlan 1-100
```

4.3 gmrp address interface

Command : gmrp {fixed|normal|forbidden} address <mac-addr> vlan <vlan-id>

interface [ethernet|port-channel] <interface-name>

Function : Make the appointed multicast address enter the mode of fixed/normal/forbidden.

Parameters: **fixed** is the mode of fixed;

normal is the normal mode;

forbidden is the mode of forbidden;

<mac-addr> is the mac address of multicast;

<vlan-id> is the number of vlan;

interface-name is the number of the port.

Command Mode: Global Mode

Default: All the multicast address table achieved dynamically belong to the normal mode.

Usage Guide: The fixed mode means the multicast flow can be achieved that the port has not to be registered and the multicast address will not aging. The normal mode means the multicast flow can be achieved when user registers on this port and the multicast address will age according to the time of leaveall. If the multicast address of forbidden mode is configured on some port, the flow of this multicast will not be transmitted to the port. Configure the address as the normal mode to delete the fixed mode and the forbidden mode.

Example: Configure the multicast address of fixed mode for the port 1/1.

```
Switch(config)#gmrp fixed address 01-00-5E-01-01-01 vlan 1 interface ethernet1/1
```

4.4 gmrp leaveall

Command: **gmrp leaveall {enable|disable}**

Function: Enable/disable leaveall timer to become due.

Command Mode: Global Mode

Default: The leaveall timer is enabled.

Usage Guide: The leaveall timer will become due normally and the multicast table will aging normally when enabling this command; the leaveall timer will not become due and the multicast table will be not deleted when disabling this command. User must enable this command unless the user wants to make the port locate in the multicast group.

Example: Enable the gmrp leaveall.

```
Switch(config)#gmrp leaveall enable
```

4.5 show gmrp fsm information

Command : show gmrp fsm information [vlan <vlan-id>] [interface [ethernet|port-channel] <interface-name>]

Function: Show the state of the property login state machine and the petition state machine.

Parameters: <vlan-id> is the number of vlan;

interface-name is the number of the port.

Command Mode: Admin Mode

Example: Look over all the multicast information of the port 1/1.

```
Switch(config)# show gmrp fsm information interface ethernet 1/1
```

VA:Very anxious Active member, AA:Anxious Active member, QA:Quiet Active member

VP:Very anxious Passive member, AP:Anxious Passive member, QP:Quiet Passive member

VO:Very anxious Observer, AO:Anxious Observer, QO:Quiet Observer

LA:Leaving Acitive member, LO:leaving Observer

IN:In, LV:Leaving, MT:Empty

INR:In Registration fixed, LVR:Leaving Registration fixed, MTR:Empty Registration fixed

INF:In Registration forbidden, LVF:Leaving Registration forbidden, MTF:Empty Registration forbidden

| Index | Vlan | Interface | Mac | Applicant | Registrar | Mode |
|-------|------|-------------|-------------------|-----------|-----------|--------|
| 1 | 1 | Ethernet1/1 | 01-00-5e-57-91-e6 | VO | MTR | Fixed |
| 2 | 1 | Ethernet1/1 | 01-00-5e-57-91-e7 | VO | MT | Normal |

4.6 show gmrp leaveall fsm information

Command : show gmrp leaveall fsm information [vlan <vlan-id>] [interface [ethernet|port-channel] <interface-name>]

Function: Show the state of leaveall of the appointed port or all ports, the appointed vlan or all vlan.

Parameters: <vlan-id> is the number of vlan;

interface-name is the number of the port.

Command Mode: Admin Mode

Example:

```
Switch(config) # show gmrp leaveall fsm information interface ethernet1/1
```

| Index | Vlan | Interface | LeaveAll fsm |
|-------|------|-------------|--------------|
| <hr/> | | | |
| 1 | 1 | Ethernet1/1 | Active |
| 2 | 3 | Ethernet1/1 | Passive |

4.7 show gmrp vlan

Command: Show gmrp vlan

Function: Show all vlan which enabled GMRP currently.

Command Mode: Admin Mode

Example:

```
Switch (config)# show gmrp vlan
```

Vlans which are enabled gmrp include::

Vlan 100

Vlan 300

4.8 show gmrp port-member

Command: show gmrp port-member [active vlan <vlan-id>]

Function: Show all ports which enabled GMRP or enabled GMRP to the movement state.

Parameters: <vlan-id> is the number of vlan.

Command Mode: Admin Mode

Example:

```
Switch(config) # show gmrp port-member
```

Ports which are enabled gmrp include:

Ethernet1/3

Ethernet1/4

Ethernet1/7

Ethernet1/9

4.9 show gmrp leavetimer running-information

Command: show gmrp leavetimer running-information [vlan <vlan-id>] [interface

[ethernet|port-channel] <interface-name>

Function: Show the moving information of leavetimer of the appointed port or all ports, the appointed vlan or all vlan.

Parameters: <vlan-id> is the number of vlan;

interface-name is the number of the port.

Command Mode: Admin Mode

Example:

```
Switch(config) # show gmrp leavetimer running-information interface ethernet 1/1
```

| Index | Vlan | Interface | Mac | Running state | Expired time |
|-------|------|-------------|-------------------|---------------|--------------|
| 1 | 100 | Ethernet1/1 | 01-00-5e-57-91-e6 | UP | 200(ms) |
| 2 | 300 | Ethernet1/1 | 01-00-5e-57-91-e5 | DOWN | non |

4.10 show gmrp running-information

Command: show gmrp {jointimer|leavealltimer} running-information [vlan <vlan-id>]

[interface [ethernet|port-channel] <interface-name>]

Function: Show the moving information of join|leaveAll timer of the appointed port or all ports, the appointed vlan or all vlan.

Parameters: <vlan-id> is the number of vlan;

interface-name is the number of the port.

Command Mode: Admin Mode

Example:

```
Switch(config)# show gmrp jointimer running-information interface ethernet 1/1
```

| Index | Vlan | Interface | Running state | Expired time |
|-------|------|-------------|---------------|--------------|
| 1 | 100 | Ethernet1/1 | UP | 200(ms) |
| 2 | 300 | Ethernet1/1 | DOWN | non |

4.11 debug gmrp packet interface

Command: debug gmrp packet {receive|send} interface [ethernet|port-channel] <interface-name>

no debug gmrp packet {receive|send} interface [ethernet|port-channel] <interface-name>

Function: Enable the gmrp packet debugging information on-off.

Parameters: **receive:** inception of packet

Send: send of packet

Command Mode: Admin Mode

Example:

```
Switch# debug gmrp packet receive interface ethernet 1/1
Receive gmrp packet, vlan 100, interface Ethernet1/1, smac 00-21-27-aa-0f-46, dmac
01-80-C2-00-00-20, length 37, dsap 0x42, ssap 0x42, ctrl 0x3
protocol id is 0x0001
```

| type | length | event | value |
|------|--------|-----------|-------------------|
| 1 | 8 | joinIn | 01-00-5e-57-91-e5 |
| 2 | 3 | joinEmpty | 1 |
| 1 | 8 | leaveln | 01-00-5e-57-91-e7 |
| 3 | 2 | leaveAll | NULL |

| type | length | event | value |
|------|--------|-----------|-------------------|
| 1 | 8 | joinIn | 01-00-5e-57-91-e5 |
| 2 | 3 | joinEmpty | 1 |
| 1 | 8 | leaveln | 01-00-5e-57-91-e7 |
| 3 | 2 | leaveAll | NULL |

4.12 debug gmrp interface

```
Command : debug gmrp {fsm|event} interface [ethernet|port-channel]
<interface-name>
      no debug gmrp {fsm|event} interface [ethernet|port-channel]
<interface-name>
```

Function: Enable gmrp state machine/event debugging information on-off including state machine transferring and the event information.

Command Mode: Admin Mode

Example:

```
Switch # debug gmrp event interface ethernet 1/1
% sep 15 02:35:15 2011 gmrp event: IndLeave created by leavetimer expired in interface
Ethernet1/1 vlan 100 for 01-00-5e-57-91-e5
% sep 15 02:35:18 2011 gmrp event: gid leaveAll timer expired in interface
Ethernet1/1/vlan 200
% sep 15 02:35:19 2011 gmrp event: fdb forward successfully in interface Ethernet1/2
vlan 100 for 01-00-5e-57-91-e5
% sep 15 02:35:15 2011 gmrp event: start gid leaveAll timer in interface Ethernet 1/1 vlan
100
```

4.13 debug gmrp error

Command: `debug gmrp error`

`no debug gmrp error`

Function: Enable/disable the debugging information of gmrp packet that is resolved wrong.

Command Mode: Admin Mode

Example:

```
Switch#debug gmrp error
```

```
%Jan 02 00:06:07 2010 %error: gmrp receive pkt contain error attribute value
```

```
%Jan 02 00:06:08 2010 %error: gmrp receive pkt contain error attribute value
```